


**STATE OF UTAH**  
DEPARTMENT OF NATURAL RESOURCES  
DIVISION OF OIL, GAS AND MINING

FORM 3

AMENDED REPORT ☐

|   |                  |                    |               |  |  |  |                            |   |              |                                    |               |                 |  |
|---|------------------|--------------------|---------------|--|--|--|----------------------------|---|--------------|------------------------------------|---------------|-----------------|--|
| <b>APPLICATION FOR PERMIT TO DRILL</b>  |                  |                    |               |  |  | <b>1. WELL NAME and NUMBER</b><br>GMBU V-6-9-17                            |                            |   |              |                                    |               |                 |  |
| <b>2. TYPE OF WORK</b><br>DRILL NEW WELL <input checked="" type="checkbox"/> REENTER P&A WELL <input type="checkbox"/> DEEPEN WELL <input type="checkbox"/> |                  |                    |               |  |  | <b>3. FIELD OR WILDCAT</b><br>MONUMENT BUTTE                               |                            |   |              |                                    |               |                 |  |
| <b>4. TYPE OF WELL</b><br>Oil Well Coalbed Methane Well: NO   |                  |                    |               |  |  | <b>5. UNIT or COMMUNITIZATION AGREEMENT NAME</b><br>GMBU (GRRV)            |                            |   |              |                                    |               |                 |  |
| <b>6. NAME OF OPERATOR</b><br>NEWFIELD PRODUCTION COMPANY   |                  |                    |               |  |  | <b>7. OPERATOR PHONE</b><br>435 646-4825                                   |                            |   |              |                                    |               |                 |  |
| <b>8. ADDRESS OF OPERATOR</b><br>Rt 3 Box 3630 , Myton, UT, 84052   |                  |                    |               |  |  | <b>9. OPERATOR E-MAIL</b><br>mcrozier@newfield.com                         |                            |   |              |                                    |               |                 |  |
| <b>10. MINERAL LEASE NUMBER (FEDERAL, INDIAN, OR STATE)</b><br>UTU-44426  |                  |                    |               | <b>11. MINERAL OWNERSHIP</b><br>FEDERAL <input checked="" type="checkbox"/> INDIAN <input type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/>    |  |  |                            | <b>12. SURFACE OWNERSHIP</b><br>FEDERAL <input checked="" type="checkbox"/> INDIAN <input type="checkbox"/> STATE <input type="checkbox"/> FEE <input type="checkbox"/> |              |                                    |               |                 |  |
| <b>13. NAME OF SURFACE OWNER (if box 12 = 'fee')</b>  |                  |                    |               |  |  | <b>14. SURFACE OWNER PHONE (if box 12 = 'fee')</b>                         |                            |   |              |                                    |               |                 |  |
| <b>15. ADDRESS OF SURFACE OWNER (if box 12 = 'fee')</b>   |                  |                    |               |  |  | <b>16. SURFACE OWNER E-MAIL (if box 12 = 'fee')</b>                        |                            |   |              |                                    |               |                 |  |
| <b>17. INDIAN ALLOTTEE OR TRIBE NAME (if box 12 = 'INDIAN')</b>   |                  |                    |               | <b>18. INTEND TO COMMINGLE PRODUCTION FROM MULTIPLE FORMATIONS</b><br>YES <input type="checkbox"/> (Submit Commingling Application) NO <input checked="" type="checkbox"/> |  |  |                            | <b>19. SLANT</b><br>VERTICAL <input type="checkbox"/> DIRECTIONAL <input checked="" type="checkbox"/> HORIZONTAL <input type="checkbox"/>                               |              |                                    |               |                 |  |
| <b>20. LOCATION OF WELL</b>   |                  | <b>FOOTAGES</b>    |               | <b>QTR-QTR</b>   |  | <b>SECTION</b>   |                            | <b>TOWNSHIP</b>   |              | <b>RANGE</b>                       |               | <b>MERIDIAN</b> |  |
| LOCATION AT SURFACE   |                  | 722 FNL 673 FEL    |               | NENE   |  | 7  |                            | 9.0 S   |              | 17.0 E                             |               | S               |  |
| Top of Uppermost Producing Zone   |                  | 253 FNL 1131 FEL   |               | NENE   |  | 7  |                            | 9.0 S   |              | 17.0 E                             |               | S               |  |
| At Total Depth  |                  | 248 FSL 1585 FEL   |               | SWSE   |  | 6  |                            | 9.0 S   |              | 17.0 E                             |               | S               |  |
| <b>21. COUNTY</b><br>DUCESNE  |                  |                    |               | <b>22. DISTANCE TO NEAREST LEASE LINE (Feet)</b><br>248  |  |  |                            | <b>23. NUMBER OF ACRES IN DRILLING UNIT</b><br>20   |              |                                    |               |                 |  |
|   |                  |                    |               | <b>25. DISTANCE TO NEAREST WELL IN SAME POOL (Applied For Drilling or Completed)</b><br>954  |  |  |                            | <b>26. PROPOSED DEPTH</b><br>MD: 6172 TVD: 6172   |              |                                    |               |                 |  |
| <b>27. ELEVATION - GROUND LEVEL</b><br>5282   |                  |                    |               | <b>28. BOND NUMBER</b><br>WYB000493  |  |  |                            | <b>29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE</b><br>437478  |              |                                    |               |                 |  |
| <b>Hole, Casing, and Cement Information</b>   |                  |                    |               |  |  |  |                            |   |              |                                    |               |                 |  |
| <b>String</b>   | <b>Hole Size</b> | <b>Casing Size</b> | <b>Length</b> | <b>Weight</b>  | <b>Grade &amp; Thread</b>  | <b>Max Mud Wt.</b>   | <b>Cement</b>              |   | <b>Sacks</b> | <b>Yield</b>                       | <b>Weight</b> |                 |  |
| Surf  | 12.25            | 8.625              | 0 - 300       | 24.0   | J-55 ST&C  | 8.3  | Class G                    |   | 138          | 1.17                               | 15.8          |                 |  |
| Prod  | 7.875            | 5.5                | 0 - 6172      | 15.5   | J-55 LT&C  | 8.3  | Premium Lite High Strength |   | 288          | 3.26                               | 11.0          |                 |  |
|   |                  |                    |               |  |  |  | 50/50 Poz                  |   | 363          | 1.24                               | 14.3          |                 |  |
| <b>ATTACHMENTS</b>  |                  |                    |               |  |  |  |                            |   |              |                                    |               |                 |  |
| <b>VERIFY THE FOLLOWING ARE ATTACHED IN ACCORDANCE WITH THE UTAH OIL AND GAS CONSERVATION GENERAL RULES</b>   |                  |                    |               |  |  |  |                            |   |              |                                    |               |                 |  |
| <input checked="" type="checkbox"/> WELL PLAT OR MAP PREPARED BY LICENSED SURVEYOR OR ENGINEER  |                  |                    |               |  |  | <input checked="" type="checkbox"/> COMPLETE DRILLING PLAN                 |                            |   |              |                                    |               |                 |  |
| <input type="checkbox"/> AFFIDAVIT OF STATUS OF SURFACE OWNER AGREEMENT (IF FEE SURFACE)  |                  |                    |               |  |  | <input type="checkbox"/> FORM 5. IF OPERATOR IS OTHER THAN THE LEASE OWNER |                            |   |              |                                    |               |                 |  |
| <input checked="" type="checkbox"/> DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OR HORIZONTALLY DRILLED)  |                  |                    |               |  |  | <input checked="" type="checkbox"/> TOPOGRAPHICAL MAP                      |                            |   |              |                                    |               |                 |  |
| <b>NAME</b> Mandie Crozier  |                  |                    |               |  | <b>TITLE</b> Regulatory Tech   |  |                            |   |              | <b>PHONE</b> 435 646-4825          |               |                 |  |
| <b>SIGNATURE</b>  |                  |                    |               |  | <b>DATE</b> 04/14/2011   |  |                            |   |              | <b>EMAIL</b> mcrozier@newfield.com |               |                 |  |
| <b>API NUMBER ASSIGNED</b><br>43013506840000  |                  |                    |               |  | <b>APPROVAL</b><br><br>Permit Manager |  |                            |   |              |                                    |               |                 |  |

NEWFIELD PRODUCTION COMPANY  
GMBU V-6-9-17  
AT SURFACE: NE/NE SECTION 7, T9S, R17E  
DUCHESNE COUNTY, UTAH

TEN POINT DRILLING PROGRAM

1. **GEOLOGIC SURFACE FORMATION:**

Uinta formation of Upper Eocene Age

2. **ESTIMATED TOPS OF IMPORTANT GEOLOGIC MARKERS:**

|                    |              |
|--------------------|--------------|
| Uinta              | 0' – 1375'   |
| Green River        | 1375'        |
| Wasatch            | 5995'        |
| <b>Proposed TD</b> | <b>6172'</b> |

3. **ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS OR MINERALS:**

Green River Formation (Oil) 1375' – 5995'

Fresh water may be encountered in the Uinta Formation, but would not be expected below about 350'. All water shows and water bearing geologic units shall be reported to the geologic and engineering staff of the Vernal Office prior to running the next string of casing or before plugging orders are requested. All water shows must be reported within one (1) business day after being encountered.

All usable (<10,000 PPM TDS) water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling will be recorded by depth and adequately protected. This information shall be reported to the Vernal Office.

Detected water flows shall be sampled, analyzed, and reported to the geologic & engineering staff of the Vernal Office. The office may request additional water samples for further analysis. Usage of the State of Utah form *Report of Water Encountered* is acceptable, but not required.

The following information is requested for water shows and samples where applicable:

|  |   |
|--|---|
| Location & Sampled Interval                        | Date Sampled                                  |
| Flow Rate  | Temperature                                   |
| Hardness   | pH  |
| Water Classification (State of Utah)               | Dissolved Calcium (Ca) (mg/l)                 |
| Dissolved Iron (Fe) (ug/l)                         | Dissolved Sodium (Na) (mg/l)                  |
| Dissolved Magnesium (Mg) (mg/l)                    | Dissolved Carbonate (CO <sub>3</sub> ) (mg/l) |
| Dissolved Bicarbonate (NaHCO <sub>3</sub> ) (mg/l) | Dissolved Chloride (Cl) (mg/l)                |
| Dissolved Sulfate (SO <sub>4</sub> ) (mg/l)        | Dissolved Total Solids (TDS) (mg/l)           |

4. **PROPOSED CASING PROGRAM**

a. **Casing Design: GMBU V-6-9-17**

| Size                     | Interval |        | Weight | Grade | Coupling | Design Factors |                |                  |
|--------------------------|----------|--------|--------|-------|----------|----------------|----------------|------------------|
|                          | Top      | Bottom |        |       |          | Burst          | Collapse       | Tension          |
| Surface casing<br>8-5/8" | 0'       | 300'   | 24.0   | J-55  | STC      | 2,950<br>17.53 | 1,370<br>14.35 | 244,000<br>33.89 |
| Prod casing<br>5-1/2"    | 0'       | 6,172' | 15.5   | J-55  | LTC      | 4,810<br>2.45  | 4,040<br>2.06  | 217,000<br>2.27  |

Assumptions:

- 1) Surface casing max anticipated surface press (MASP) = Frac gradient – gas gradient
- 2) Prod casing MASP (production mode) = Pore pressure – gas gradient
- 3) All collapse calculations assume fully evacuated casing w/ gas gradient
- 4) All tension calculations assume air weight

|  |              |
|--|--------------|
| Frac gradient at surface casing shoe = | 13.0 ppg     |
| Pore pressure at surface casing shoe = | 8.33 ppg     |
| Pore pressure at prod casing shoe =    | 8.33 ppg     |
| Gas gradient =                         | 0.115 psi/ft |

All casing shall be new or, if used, inspected and tested. Used casing shall meet or exceed API standards for new casing.

All casing strings shall have a minimum of 1 (one) centralizer on each of the bottom three (3) joints.

b. **Cementing Design: GMBU V-6-9-17**

| Job                 | Fill   | Description                         | Sacks           | OH<br>Excess* | Weight<br>(ppg) | Yield<br>(ft <sup>3</sup> /sk) |
|---------------------|--------|-------------------------------------|-----------------|---------------|-----------------|--------------------------------|
|                     |        |                                     | ft <sup>3</sup> |               |                 |                                |
| Surface casing      | 300'   | Class G w/ 2% CaCl                  | 138<br>161      | 30%           | 15.8            | 1.17                           |
| Prod casing<br>Lead | 4,172' | Prem Lite II w/ 10% gel + 3%<br>KCl | 288<br>940      | 30%           | 11.0            | 3.26                           |
| Prod casing<br>Tail | 2,000' | 50/50 Poz w/ 2% gel + 3%<br>KCl     | 363<br>451      | 30%           | 14.3            | 1.24                           |

\*Actual volume pumped will be 15% over the caliper log

- Compressive strength of lead cement: 1800 psi @ 24 hours, 2250 psi @ 72 hours
- Compressive strength of tail cement: 2500 psi @ 24 hours

Hole Sizes: A 12-1/4" hole will be drilled for the 8-5/8" surface casing. A 7-7/8" hole will be drilled for the 5-1/2" production casing.

The 8-5/8" surface casing shall in all cases be cemented back to surface. In the event that during the primary surface cementing operation the cement does not circulate to surface, or if the cement level should fall back more than 8 feet from surface, then a remedial surface cementing operation shall be performed to insure adequate isolation and stabilization of the surface casing.

5. **MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:**

The operator's minimum specifications for pressure control equipment are as follows:

An 8" Double Ram Hydraulic unit with a closing unit will be utilized. Function test of BOP's will be check daily.

Refer to **Exhibit C** for a diagram of BOP equipment that will be used on this well.

6. **TYPE AND CHARACTERISTICS OF THE PROPOSED CIRCULATION MUDS:**

From surface to  $\pm 350$  feet will be drilled with an air/mist system. The air rig is equipped with a 6 1/2" blooie line that is straight run and securely anchored. The blooie line is used with a discharge less than 100 ft from the wellbore in order to minimize the well pad size. The blooie line is not equipped with an automatic igniter or continuous pilot light and the compressor is located less than 100 ft from the well bore due to the low possibility of combustion with the air dust mixture. The trailer mounted compressor (capacity of 2000 CFM) has a safety shut-off valve which is located 15 feet from the air rig. A truck with 70 bbls of water is on stand by to be used as kill fluid, if necessary. From about  $\pm 350$  feet to TD, a fresh water system will be utilized. Clay inhibition and hole stability will be achieved with a KCl substitute additive. This additive will be identified in the APD and reviewed to determine if the reserve pit shall be lined. This fresh water system will typically contain Total Dissolved Solids (TDS) of less than 3000 PPM. Anticipated mud weight is 8.4 lbs/gal. If necessary to control formation fluids or pressure, the system will be weighted with the addition of bentonite gel, and if pressure conditions warrant, with barite

No chromate additives will be used in the mud system on Federal and/or Indian lands without prior BLM approval to ensure adequate protection of fresh aquifers.

No chemicals subject to reporting under SARA Title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completing of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completing of this well.

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

Newfield Production will **visually** monitor pit levels and flow from the well during drilling operations.

7. **AUXILIARY SAFETY EQUIPMENT TO BE USED:**

Auxiliary safety equipment will be a Kelly Cock, bit float, and a TIW valve with drill pipe threads.

8. **TESTING, LOGGING AND CORING PROGRAMS:**

The logging program will consist of a Dual Induction, Gamma Ray and Caliper log from TD to base of surface casing @ 300' +/-, and a Compensated Neutron-Formation Density Log from TD to 3500' +/- . A cement bond log will be run from PBTD to cement top. No drill stem testing or coring is planned for this well.

9. **ANTICIPATED ABNORMAL PRESSURE OR TEMPERATURE:**


No abnormal temperatures or pressures are anticipated. No hydrogen sulfide has been encountered or is known to exist from previous drilling in the area at this depth. Maximum anticipated bottomhole pressure will approximately equal total depth in feet multiplied by a 0.433 psi/foot gradient.

10. **ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS:**

It is anticipated that the drilling operations will commence the third quarter of 2011, and take approximately seven (7) days from spud to rig release.

*T9S, R17E, S.L.B.&M.*

**NEWFIELD EXPLORATION COMPANY**



 = SECTION CORNERS LOCATED

BASIS OF ELEV; Elevations are base on  
LOCATION: an N.G.S. OPUS Correction.  
LAT. 40°04'09.56" LONG. 110°00'43.28"  
(Tristate Aluminum Cap) Elev. 5281.57'

V-6-9-17  
(Surface Location) NAD 83  
LATITUDE = 40° 03' 02.37"  
LONGITUDE = 110° 02' 32.29"

WELL LOCATION, V-6-9-17, LOCATED  
AS SHOWN IN THE NE 1/4 NE 1/4 OF  
SECTION 7, T9S, R17E, S.L.B.&M.  
DUCESNE COUNTY, UTAH.



NOTES:

1. Well footages are measured at right angles to the Section Lines.
2. Bearings are based on Global Positioning Satellite observations.

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS  
PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS  
MADE BY ME OR UNDER MY SUPERVISION AND THAT  
THE SAME ARE TRUE AND CORRECT TO THE BEST  
OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR  
REGISTRATION No. 100377  
STATE OF UTAH


**TRI STATE LAND SURVEYING & CONSULTING**  
180 NORTH VERNAL AVE. — VERNAL, UTAH 84078  
(435) 781-2501

|                            |                   |
|----------------------------|-------------------|
| DATE SURVEYED:<br>07-21-10 | SURVEYED BY: D.G. |
| DATE DRAWN:<br>01-20-11    | DRAWN BY: M.W.    |
| REVISED:                   | SCALE: 1" = 1000' |



# T9S, R17E, S.L.B.&M.

## NEWFIELD EXPLORATION COMPANY




TARGET BOTTOM HOLE, V-6-9-17,  
LOCATED AS SHOWN IN THE SW 1/4 SE  
1/4 OF SECTION 6, T9S, R17E,  
S.L.B.&M. DUCHESNE COUNTY, UTAH.



### NOTES:

1. Well footages are measured at right angles to the Section Lines.
2. Bearings are based on Global Positioning Satellite observations.
3. The Center of Pattern footages are 30' FSL 1380' FEL.
4. The Bottom of Hole footages are 248' FSL & 1585' FEL.

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS  
PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS  
MADE BY ME OR UNDER MY SUPERVISION AND THAT  
THE SAME ARE TRUE AND CORRECT TO THE BEST  
OF MY KNOWLEDGE AND BELIEF.



### TRI STATE LAND SURVEYING & CONSULTING


180 NORTH VERNAL AVE. - VERNAL, UTAH 84078  
(435) 781-2501

|                            |                   |
|----------------------------|-------------------|
| DATE SURVEYED:<br>07-21-10 | SURVEYED BY: D.G. |
| DATE DRAWN:<br>09-23-10    | DRAWN BY: M.W.    |
| REVISED:                   | SCALE: 1" = 1000' |

◆ = SECTION CORNERS LOCATED

BASIS OF ELEV; Elevations are base on  
LOCATION: an N.G.S. OPUS Correction.  
LAT. 40°04'09.56" LONG. 110°00'43.28"  
(Tristate Aluminum Cap) Elev. 5281.57'

# Access Road Map



**Tri State**  
**Land Surveying, Inc.**

180 NORTH VERNAL AVE. VERNAL, UTAH 84078

P: (435) 781-2501  
 F: (435) 781-2518



## NEWFIELD EXPLORATION COMPANY

V-6-9-17 (Proposed Well)  
 F-8-9-17 (Proposed Well)  
 7A-7-9-17 (Existing Well)

SEC. 7, T9S, R17E, S.L.B.&M. Duchesne County, UT.

**TOPOGRAPHIC MAP**

SHEET  
**A**

RECEIVED: Apr. 14, 2011

|           |            |          |            |
|-----------|------------|----------|------------|
| DRAWN BY: | C.H.M.     | REVISED: | 11-15-2010 |
| DATE:     | 07-30-2010 | REVISED: | 01-20-2011 |
| SCALE:    | 1:100,000  |          |            |



Existing Road



**Tri State**  
**Land Surveying, Inc.**

N




|           |             |          |            |
|-----------|-------------|----------|------------|
| DRAWN BY: | C.H.M.      | REVISED: | 11-15-2010 |
| DATE:     | 07-30-2010  | REVISED: | 01-20-2011 |
| SCALE:    | 1" = 2,000' |          |            |

SHEET

B

**RECEIVED:** Apr. 14, 2011

# Proposed Pipeline Map



## Legend

- Existing Road
- Proposed Flowline



**Tri State**  
Land Surveying, Inc.

180 NORTH VERNAL AVE. VERNAL, UTAH 84078

P: (435) 781-2501  
F: (435) 781-2518



## NEWFIELD EXPLORATION COMPANY

V-6-9-17 (Proposed Well)  
F-8-9-17 (Proposed Well)  
7A-7-9-17 (Existing Well)

SEC. 7, T9S, R17E, S.L.B.&M. Duchesne County, UT.

|           |             |          |            |
|-----------|-------------|----------|------------|
| DRAWN BY: | C.H.M.      | REVISED: | 11-15-2010 |
| DATE:     | 07-30-2010  | REVISED: | 01-20-2011 |
| SCALE:    | 1" = 2,000' |          |            |


TOPOGRAPHIC MAP

SHEET

C

RECEIVED: Apr. 14, 2011








# Exhibit "B" Map

V-6-9-17 (Proposed Well)  
F-8-9-17 (Proposed Well)  
7A-7-9-17 (Existing Well)



## Legend

- 1 Mile Radius
- Pad Location



**Tri State**  
**Land Surveying, Inc.**

180 NORTH VERNAL AVE. VERNAL, UTAH 84078

P: (435) 781-2501  
F: (435) 781-2518



## NEWFIELD EXPLORATION COMPANY

V-6-9-17 (Proposed Well)  
F-8-9-17 (Proposed Well)  
7A-7-9-17 (Existing Well)

SEC. 7, T9S, R17E, S.L.B.&M. Duchesne County, UT.

|           |             |          |            |
|-----------|-------------|----------|------------|
| DRAWN BY: | C.H.M.      | REVISED: | 11-15-2010 |
| DATE:     | 07-30-2010  | REVISED: | 01-20-2011 |
| SCALE:    | 1" = 2,000' |          |            |

**TOPOGRAPHIC MAP**

SHEET

**D**

RECEIVED: Apr. 14, 2011





## **NEWFIELD EXPLORATION**

**USGS Myton SW (UT)  
SECTION 34 T8S, R17E  
V-6-9-17**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report**

**19 January, 2011**





## PayZone Directional Services, LLC.

## Planning Report



|                  |                            |                                     |                                    |
|------------------|----------------------------|-------------------------------------|------------------------------------|
| <b>Database:</b> | EDM 2003.21 Single User Db | <b>Local Co-ordinate Reference:</b> | Well V-6-9-17                      |
| <b>Company:</b>  | NEWFIELD EXPLORATION       | <b>TVD Reference:</b>               | V-6-9-17 @ 5294.0ft (Newfield Rig) |
| <b>Project:</b>  | USGS Myton SW (UT)         | <b>MD Reference:</b>                | V-6-9-17 @ 5294.0ft (Newfield Rig) |
| <b>Site:</b>     | SECTION 34 T8S, R17E       | <b>North Reference:</b>             | True                               |
| <b>Well:</b>     | V-6-9-17                   | <b>Survey Calculation Method:</b>   | Minimum Curvature                  |
| <b>Wellbore:</b> | Wellbore #1                |                                     |                                    |
| <b>Design:</b>   | Design #1                  |                                     |                                    |

|                    |  |                      |                |
|--------------------|--|----------------------|----------------|
| <b>Project</b>     | USGS Myton SW (UT), DUCHESNE COUNTY, UT, USA |                      |                |
| <b>Map System:</b> | US State Plane 1983                          | <b>System Datum:</b> | Mean Sea Level |
| <b>Geo Datum:</b>  | North American Datum 1983                    |                      |                |
| <b>Map Zone:</b>   | Utah Central Zone                            |                      |                |

|                       |                      |              |                 |                   |                   |
|-----------------------|----------------------|--------------|-----------------|-------------------|-------------------|
| Site                  | SECTION 34 T8S, R17E |              |                 |                   |                   |
| Site Position:        |                      | Northing:    | 7,199,300.00 ft | Latitude:         | 40° 4' 27.066 N   |
| From:                 | Lat/Long             | Easting:     | 2,062,202.62 ft | Longitude:        | 109° 59' 33.558 W |
| Position Uncertainty: | 0.0 ft               | Slot Radius: | "               | Grid Convergence: | 0.97 °            |

|                      |   |              |                     |                 |               |                  |
|----------------------|---|--------------|---------------------|-----------------|---------------|------------------|
| Well                 | V-6-9-17, SHL LAT: 40 03 02.37 LONG -110 02 32.29 |              |                     |                 |               |                  |
| Well Position        | +N/-S   | -8,573.6 ft  | Northing:           | 7,190,501.11 ft | Latitude:     | 40° 3' 2.370 N   |
|                      | +E/-W   | -13,893.1 ft | Easting:            | 2,048,451.09 ft | Longitude:    | 110° 2' 32.290 W |
| Position Uncertainty |   | 0.0 ft       | Wellhead Elevation: | 5,294.0 ft      | Ground Level: | 5,282.0 ft       |

|                  |                   |                    |                        |                      |                            |
|------------------|-------------------|--------------------|------------------------|----------------------|----------------------------|
| <b>Wellbore</b>  | Wellbore #1       |                    |                        |                      |                            |
| <b>Magnetics</b> | <b>Model Name</b> | <b>Sample Date</b> | <b>Declination (°)</b> | <b>Dip Angle (°)</b> | <b>Field Strength (nT)</b> |
|                  | IGRF2010          | 2011/01/19         | 11.36                  | 65.81                | 52,318                     |

|                          |                              |                   |                      |                      |
|--------------------------|------------------------------|-------------------|----------------------|----------------------|
| <b>Design</b>            | Design #1                    |                   |                      |                      |
| <b>Audit Notes:</b>      |                              |                   |                      |                      |
| <b>Version:</b>          | <b>Phase:</b>                | PROTOTYPE         | <b>Tie On Depth:</b> | 0.0                  |
| <b>Vertical Section:</b> | <b>Depth From (TVD) (ft)</b> | <b>+N/-S (ft)</b> | <b>+E/-W (ft)</b>    | <b>Direction (°)</b> |
|                          | 4,900.0                      | 0.0               | 0.0                  | 315.73               |

| Plan Sections       |                 |             |                     |            |            |                       |                      |                     |         |              |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|----------------------|---------------------|---------|--------------|
| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) | TFO (°) | Target       |
| 0.0                 | 0.00            | 0.00        | 0.0                 | 0.0        | 0.0        | 0.00                  | 0.00                 | 0.00                | 0.00    |              |
| 600.0               | 0.00            | 0.00        | 600.0               | 0.0        | 0.0        | 0.00                  | 0.00                 | 0.00                | 0.00    |              |
| 1,615.1             | 15.23           | 315.73      | 1,603.2             | 96.0       | -93.6      | 1.50                  | 1.50                 | 0.00                | 315.73  |              |
| 5,031.9             | 15.23           | 315.73      | 4,900.0             | 738.6      | -720.0     | 0.00                  | 0.00                 | 0.00                | 0.00    | V-6-9-17 TGT |
| 6,171.9             | 15.23           | 315.73      | 6,000.0             | 953.0      | -929.0     | 0.00                  | 0.00                 | 0.00                | 0.00    |              |



## PayZone Directional Services, LLC.

## Planning Report



|                  |                            |                                     |                                    |
|------------------|----------------------------|-------------------------------------|------------------------------------|
| <b>Database:</b> | EDM 2003.21 Single User Db | <b>Local Co-ordinate Reference:</b> | Well V-6-9-17                      |
| <b>Company:</b>  | NEWFIELD EXPLORATION       | <b>TVD Reference:</b>               | V-6-9-17 @ 5294.0ft (Newfield Rig) |
| <b>Project:</b>  | USGS Myton SW (UT)         | <b>MD Reference:</b>                | V-6-9-17 @ 5294.0ft (Newfield Rig) |
| <b>Site:</b>     | SECTION 34 T8S, R17E       | <b>North Reference:</b>             | True                               |
| <b>Well:</b>     | V-6-9-17                   | <b>Survey Calculation Method:</b>   | Minimum Curvature                  |
| <b>Wellbore:</b> | Wellbore #1                |                                     |                                    |
| <b>Design:</b>   | Design #1                  |                                     |                                    |

## Planned Survey

| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Vertical Section (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|-----------------------|----------------------|---------------------|
| 0.0                 | 0.00            | 0.00        | 0.0                 | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 100.0               | 0.00            | 0.00        | 100.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 200.0               | 0.00            | 0.00        | 200.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 300.0               | 0.00            | 0.00        | 300.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 400.0               | 0.00            | 0.00        | 400.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 500.0               | 0.00            | 0.00        | 500.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 600.0               | 0.00            | 0.00        | 600.0               | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 700.0               | 1.50            | 315.73      | 700.0               | 0.9        | -0.9       | 1.3                   | 1.50                  | 1.50                 | 0.00                |
| 800.0               | 3.00            | 315.73      | 799.9               | 3.7        | -3.7       | 5.2                   | 1.50                  | 1.50                 | 0.00                |
| 900.0               | 4.50            | 315.73      | 899.7               | 8.4        | -8.2       | 11.8                  | 1.50                  | 1.50                 | 0.00                |
| 1,000.0             | 6.00            | 315.73      | 999.3               | 15.0       | -14.6      | 20.9                  | 1.50                  | 1.50                 | 0.00                |
| 1,100.0             | 7.50            | 315.73      | 1,098.6             | 23.4       | -22.8      | 32.7                  | 1.50                  | 1.50                 | 0.00                |
| 1,200.0             | 9.00            | 315.73      | 1,197.5             | 33.7       | -32.8      | 47.0                  | 1.50                  | 1.50                 | 0.00                |
| 1,300.0             | 10.50           | 315.73      | 1,296.1             | 45.8       | -44.6      | 64.0                  | 1.50                  | 1.50                 | 0.00                |
| 1,400.0             | 12.00           | 315.73      | 1,394.2             | 59.8       | -58.3      | 83.5                  | 1.50                  | 1.50                 | 0.00                |
| 1,500.0             | 13.50           | 315.73      | 1,491.7             | 75.6       | -73.7      | 105.5                 | 1.50                  | 1.50                 | 0.00                |
| 1,600.0             | 15.00           | 315.73      | 1,588.6             | 93.2       | -90.9      | 130.2                 | 1.50                  | 1.50                 | 0.00                |
| 1,615.1             | 15.23           | 315.73      | 1,603.2             | 96.0       | -93.6      | 134.1                 | 1.50                  | 1.50                 | 0.00                |
| 1,700.0             | 15.23           | 315.73      | 1,685.1             | 112.0      | -109.2     | 156.4                 | 0.00                  | 0.00                 | 0.00                |
| 1,800.0             | 15.23           | 315.73      | 1,781.6             | 130.8      | -127.5     | 182.7                 | 0.00                  | 0.00                 | 0.00                |
| 1,900.0             | 15.23           | 315.73      | 1,878.1             | 149.6      | -145.8     | 208.9                 | 0.00                  | 0.00                 | 0.00                |
| 2,000.0             | 15.23           | 315.73      | 1,974.6             | 168.4      | -164.2     | 235.2                 | 0.00                  | 0.00                 | 0.00                |
| 2,100.0             | 15.23           | 315.73      | 2,071.1             | 187.2      | -182.5     | 261.4                 | 0.00                  | 0.00                 | 0.00                |
| 2,200.0             | 15.23           | 315.73      | 2,167.6             | 206.0      | -200.8     | 287.7                 | 0.00                  | 0.00                 | 0.00                |
| 2,300.0             | 15.23           | 315.73      | 2,264.0             | 224.8      | -219.2     | 314.0                 | 0.00                  | 0.00                 | 0.00                |
| 2,400.0             | 15.23           | 315.73      | 2,360.5             | 243.6      | -237.5     | 340.2                 | 0.00                  | 0.00                 | 0.00                |
| 2,500.0             | 15.23           | 315.73      | 2,457.0             | 262.4      | -255.8     | 366.5                 | 0.00                  | 0.00                 | 0.00                |
| 2,600.0             | 15.23           | 315.73      | 2,553.5             | 281.2      | -274.2     | 392.8                 | 0.00                  | 0.00                 | 0.00                |
| 2,700.0             | 15.23           | 315.73      | 2,650.0             | 300.0      | -292.5     | 419.0                 | 0.00                  | 0.00                 | 0.00                |
| 2,800.0             | 15.23           | 315.73      | 2,746.5             | 318.9      | -310.8     | 445.3                 | 0.00                  | 0.00                 | 0.00                |
| 2,900.0             | 15.23           | 315.73      | 2,843.0             | 337.7      | -329.2     | 471.6                 | 0.00                  | 0.00                 | 0.00                |
| 3,000.0             | 15.23           | 315.73      | 2,939.5             | 356.5      | -347.5     | 497.8                 | 0.00                  | 0.00                 | 0.00                |
| 3,100.0             | 15.23           | 315.73      | 3,036.0             | 375.3      | -365.8     | 524.1                 | 0.00                  | 0.00                 | 0.00                |
| 3,200.0             | 15.23           | 315.73      | 3,132.5             | 394.1      | -384.2     | 550.3                 | 0.00                  | 0.00                 | 0.00                |
| 3,300.0             | 15.23           | 315.73      | 3,228.9             | 412.9      | -402.5     | 576.6                 | 0.00                  | 0.00                 | 0.00                |
| 3,400.0             | 15.23           | 315.73      | 3,325.4             | 431.7      | -420.8     | 602.9                 | 0.00                  | 0.00                 | 0.00                |
| 3,500.0             | 15.23           | 315.73      | 3,421.9             | 450.5      | -439.2     | 629.1                 | 0.00                  | 0.00                 | 0.00                |
| 3,600.0             | 15.23           | 315.73      | 3,518.4             | 469.3      | -457.5     | 655.4                 | 0.00                  | 0.00                 | 0.00                |
| 3,700.0             | 15.23           | 315.73      | 3,614.9             | 488.1      | -475.8     | 681.7                 | 0.00                  | 0.00                 | 0.00                |
| 3,800.0             | 15.23           | 315.73      | 3,711.4             | 506.9      | -494.2     | 707.9                 | 0.00                  | 0.00                 | 0.00                |
| 3,900.0             | 15.23           | 315.73      | 3,807.9             | 525.7      | -512.5     | 734.2                 | 0.00                  | 0.00                 | 0.00                |
| 4,000.0             | 15.23           | 315.73      | 3,904.4             | 544.5      | -530.8     | 760.5                 | 0.00                  | 0.00                 | 0.00                |
| 4,100.0             | 15.23           | 315.73      | 4,000.9             | 563.3      | -549.2     | 786.7                 | 0.00                  | 0.00                 | 0.00                |
| 4,200.0             | 15.23           | 315.73      | 4,097.3             | 582.1      | -567.5     | 813.0                 | 0.00                  | 0.00                 | 0.00                |
| 4,300.0             | 15.23           | 315.73      | 4,193.8             | 601.0      | -585.8     | 839.3                 | 0.00                  | 0.00                 | 0.00                |
| 4,400.0             | 15.23           | 315.73      | 4,290.3             | 619.8      | -604.2     | 865.5                 | 0.00                  | 0.00                 | 0.00                |
| 4,500.0             | 15.23           | 315.73      | 4,386.8             | 638.6      | -622.5     | 891.8                 | 0.00                  | 0.00                 | 0.00                |
| 4,600.0             | 15.23           | 315.73      | 4,483.3             | 657.4      | -640.8     | 918.0                 | 0.00                  | 0.00                 | 0.00                |
| 4,700.0             | 15.23           | 315.73      | 4,579.8             | 676.2      | -659.2     | 944.3                 | 0.00                  | 0.00                 | 0.00                |
| 4,800.0             | 15.23           | 315.73      | 4,676.3             | 695.0      | -677.5     | 970.6                 | 0.00                  | 0.00                 | 0.00                |
| 4,900.0             | 15.23           | 315.73      | 4,772.8             | 713.8      | -695.8     | 996.8                 | 0.00                  | 0.00                 | 0.00                |
| 5,000.0             | 15.23           | 315.73      | 4,869.3             | 732.6      | -714.2     | 1,023.1               | 0.00                  | 0.00                 | 0.00                |
| 5,031.9             | 15.23           | 315.73      | 4,900.0             | 738.6      | -720.0     | 1,031.5               | 0.00                  | 0.00                 | 0.00                |

V-6-9-17 TGT



## PayZone Directional Services, LLC.

## Planning Report



**Database:** EDM 2003.21 Single User Db  
**Company:** NEWFIELD EXPLORATION  
**Project:** USGS Myton SW (UT)  
**Site:** SECTION 34 T8S, R17E  
**Well:** V-6-9-17  
**Wellbore:** Wellbore #1  
**Design:** Design #1

**Local Co-ordinate Reference:** Well V-6-9-17  
**TVD Reference:** V-6-9-17 @ 5294.0ft (Newfield Rig)  
**MD Reference:** V-6-9-17 @ 5294.0ft (Newfield Rig)  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature

## Planned Survey

| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Vertical Section (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|-----------------------|----------------------|---------------------|
| 5,100.0             | 15.23           | 315.73      | 4,965.8             | 751.4      | -732.5     | 1,049.4               | 0.00                  | 0.00                 | 0.00                |
| 5,200.0             | 15.23           | 315.73      | 5,062.2             | 770.2      | -750.8     | 1,075.6               | 0.00                  | 0.00                 | 0.00                |
| 5,300.0             | 15.23           | 315.73      | 5,158.7             | 789.0      | -769.2     | 1,101.9               | 0.00                  | 0.00                 | 0.00                |
| 5,400.0             | 15.23           | 315.73      | 5,255.2             | 807.8      | -787.5     | 1,128.2               | 0.00                  | 0.00                 | 0.00                |
| 5,500.0             | 15.23           | 315.73      | 5,351.7             | 826.6      | -805.8     | 1,154.4               | 0.00                  | 0.00                 | 0.00                |
| 5,600.0             | 15.23           | 315.73      | 5,448.2             | 845.4      | -824.2     | 1,180.7               | 0.00                  | 0.00                 | 0.00                |
| 5,700.0             | 15.23           | 315.73      | 5,544.7             | 864.2      | -842.5     | 1,207.0               | 0.00                  | 0.00                 | 0.00                |
| 5,800.0             | 15.23           | 315.73      | 5,641.2             | 883.1      | -860.8     | 1,233.2               | 0.00                  | 0.00                 | 0.00                |
| 5,900.0             | 15.23           | 315.73      | 5,737.7             | 901.9      | -879.2     | 1,259.5               | 0.00                  | 0.00                 | 0.00                |
| 6,000.0             | 15.23           | 315.73      | 5,834.2             | 920.7      | -897.5     | 1,285.7               | 0.00                  | 0.00                 | 0.00                |
| 6,100.0             | 15.23           | 315.73      | 5,930.6             | 939.5      | -915.8     | 1,312.0               | 0.00                  | 0.00                 | 0.00                |
| 6,171.9             | 15.23           | 315.73      | 6,000.0             | 953.0      | -929.0     | 1,330.9               | 0.00                  | 0.00                 | 0.00                |

## Targets

| Target Name<br>- hit/miss target<br>- Shape                  | Dip Angle (°) | Dip Dir. (°) | TVD (ft) | +N/-S (ft) | +E/-W (ft) | Northing (ft) | Easting (ft) | Latitude       | Longitude        |
|--|---------------|--------------|----------|------------|------------|---------------|--------------|----------------|------------------|
| V-6-9-17 TGT<br>- plan hits target<br>- Circle (radius 75.0) | 0.00          | 0.00         | 4,900.0  | 738.6      | -720.0     | 7,191,227.87  | 2,047,719.14 | 40° 3' 9.669 N | 110° 2' 41.550 W |







Project: USGS Myton SW (UT)  
 Site: SECTION 34 T8S, R17E  
 Well: V-6-9-17  
 Wellbore: Wellbore #1  
 Design: Design #1



Azimuths to True North  
 Magnetic North: 11.36°

Magnetic Field  
 Strength: 52318.0snT  
 Dip Angle: 65.81°  
 Date: 2011/01/19  
 Model: IGRF2010

KOP @ 600'  
 DOGLEG RATE 1.5 DEG/100  
 TARGET RADIUS IS 75'



#### WELLBORE TARGET DETAILS

| Name         | TVD    | +N/-S | +E/-W  | Shape                 |
|--------------|--------|-------|--------|-----------------------|
| V-6-9-17 TGT | 4900.0 | 738.6 | -720.0 | Circle (Radius: 75.0) |

#### SECTION DETAILS

| Sec | MD     | Inc   | Azi    | TVD    | +N/-S | +E/-W  | DLeg | TFace  | VSec   | Target       |
|-----|--------|-------|--------|--------|-------|--------|------|--------|--------|--------------|
| 1   | 0.0    | 0.00  | 0.00   | 0.0    | 0.0   | 0.0    | 0.00 | 0.00   | 0.0    |              |
| 2   | 600.0  | 0.00  | 0.00   | 600.0  | 0.0   | 0.0    | 0.00 | 0.00   | 0.0    |              |
| 3   | 1615.1 | 15.23 | 315.73 | 1603.2 | 96.0  | -93.6  | 1.50 | 315.73 | 134.1  |              |
| 4   | 5031.9 | 15.23 | 315.73 | 4900.0 | 738.6 | -720.0 | 0.00 | 0.00   | 1031.5 | V-6-9-17 TGT |
| 5   | 6171.9 | 15.23 | 315.73 | 6000.0 | 953.0 | -929.0 | 0.00 | 0.00   | 1330.9 |              |



**NEWFIELD PRODUCTION COMPANY  
GMBU V-6-9-17  
AT SURFACE: NE/NE SECTION 7, T9S, R17E  
DUCHESNE COUNTY, UTAH**

**ONSHORE ORDER NO. 1**

**MULTI-POINT SURFACE USE & OPERATIONS PLAN**

**1. EXISTING ROADS**

See attached Topographic Map "A"

To reach Newfield Production Company well location site GMBU V-6-9-17 located in the NE 1/4 NE 1/4 Section 7, T9S, R17E, Duchesne County, Utah:

Proceed southwesterly out of Myton, Utah along Highway 40 - 1.4 miles  $\pm$  to the junction of this highway and UT State Hwy 53; proceed southwesterly - 10.0 miles  $\pm$  to it's junction with an existing dirt road to the southwest; proceed in a southwesterly direction - 0.9 miles  $\pm$  to it's junction with an existing road to the southeast; proceed southeasterly - 0.8 miles  $\pm$  to it's junction with an existing road to the southwest; proceed southwesterly - 1.1 miles  $\pm$  to the existing 7A-7-9-17 well location.

The aforementioned dirt oil field service roads and other roads in the vicinity are constructed out of existing native materials that are prevalent to the existing area they are located in and range from clays to a sandy-clay shale material.

The roads for access during the drilling, completion and production phase will be maintained at the standards required by the State of Utah, or other controlling agencies. This maintenance will consist of some minor grader work for smoothing road surfaces and for snow removal. Any necessary fill material for repair will be purchase and hauled from private sources.

**2. PLANNED ACCESS ROAD**

There is no proposed access road for this location. The proposed well will be drilled directionaly off of the existing 7A-7-9-17 well pad. See attached **Topographic Map "B"**.

There will be **no** culverts required along this access road. There will be barrow ditches and turnouts as needed along this road.

There are no fences encountered along this proposed road. There will be no new gates or cattle guards required.

All construction material for this access road will be borrowed material accumulated during construction of the access road.

**3. LOCATION OF EXISTING WELLS**

Refer to Exhibit "B".

**4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES**

There are no existing facilities that will be used by this well.

It is anticipated that this well will be a producing oil well.

Upon construction of a tank battery, the well pad will be surrounded by a dike of sufficient capacity to contain at minimum 110% of the largest tank volume within the facility battery.

Tank batteries will be built to State specifications.

All permanent (on site for six (6) months or longer) structures, constructed or installed (including pumping units), will be painted a flat, non-reflective, earth tone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within six months of installation.

5. **LOCATION AND TYPE OF WATER SUPPLY**

Newfield Production will transport water by truck from nearest water source as determined by a Newfield representative for the purpose of drilling the above mentioned well. The available water sources are as follows:

Johnson Water District  
Water Right : 43-10136

Maurice Harvey Pond  
Water Right: 47-1358

Neil Moon Pond  
Water Right: 43-11787

Newfield Collector Well  
Water Right: 47-1817 (A30414DVA, contracted with the Duchesne County Conservancy District).

There will be no water well drilled at this site.

6. **SOURCE OF CONSTRUCTION MATERIALS**

All construction material for this location shall be borrowed material accumulated during construction of the location site and access road.

A mineral material application is not required for this location.

7. **METHODS FOR HANDLING WASTE DISPOSAL**

A small reserve pit (90' x 40' x 8' deep, or less) will be constructed from native soil and clay materials. The reserve pit will receive the processed drill cutting (wet sand, shale & rock) removed from the wellbore. Any drilling fluids, which do accumulate in the pit as a result of shale-shaker carryover, cleaning of the sand trap, etc., will be promptly reclaimed. All drilling fluids will be fresh water based, typically containing Total Dissolved Solids of less than 3000 PPM. No potassium chloride, chromates, trash, debris, nor any other substance deemed hazardous will be placed in this pit. Therefore, it is proposed that no synthetic liner be required in the reserve pit. However, if upon constructing the pit there is insufficient fine clay and silt present, a liner will be used for the purpose of reducing water loss through percolation.

Newfield requests approval that a flare pit not be constructed or utilized on this location.

A portable toilet will be provided for human waste.

A trash basket will be provided for garbage (trash) and hauled away to an approved disposal site at the completion of the drilling activities.

8. **ANCILLARY FACILITIES**

There are no ancillary facilities planned for at the present time and none foreseen in the near future.

9. **WELL SITE LAYOUT**

See attached Location Layout Sheet.

**Fencing Requirements**

All pits will be fenced according to the following minimum standards:

- a) A 39-inch net wire shall be used with at least one strand of barbed wire on top of the net.
- b) The net wire shall be no more than two (2) inches above the ground. The barbed wire shall be three (3) inches above the net wire. Total height of the fence shall be at least forty-two (42) inches.
- c) Corner posts shall be centered and/or braced in such a manner to keep tight at all times
- d) Standard steel, wood or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than sixteen (16) feet.
- e) All wire shall be stretched, by using a stretching device, before it is attached to the corner posts.

The reserve pit fencing will be on three (3) sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until cleanup.

Existing fences to be crossed by the access road will be braced and tied off before cutting so as to prevent slacking in the wire. The opening shall be closed temporarily as necessary during construction to prevent the escape of livestock, and upon completion of construction the fence shall be repaired to BLM specifications.

10. **PLANS FOR RESTORATION OF SURFACE:**

a) Producing Location

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, material, trash and junk not required for production.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximated natural contours. Weather permitting, the reserve pit will be reclaimed within one hundred twenty (120) days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed.

b) Dry Hole Abandoned Location

At such time as the well is plugged and abandoned, the operator shall submit a subsequent report of abandonment and the State of Utah will attach the appropriate surface rehabilitation conditions of approval.

11. **SURFACE OWNERSHIP** – Bureau of Land Management.

12. **OTHER ADDITIONAL INFORMATION**



The Archaeological Resource Survey and Paleontological Resource Survey for this area are attached. MOAC Report #10-215, 1/10/11. Paleontological Resource Survey prepared by, Wade E. Miller, 9/27/10. See attached report cover pages, Exhibit "D".

#### **Surface Flow Line**

Newfield requests 1729' of surface flow line be granted. The Surface Flow Line will consist of up to a 14" bundled pipe consisting of 2-2" poly glycol lines and 1-3" production line. For all new wells, Newfield. **Refer to Topographic Map "C"** for the proposed location of the proposed flow line. Flow lines will be tan and will be constructed using the following procedures:

Clearing and Grading: No clearing or grading of the ROW will be required. The centerline of the proposed route will be staked prior to installation. Flow lines shall be placed as close to existing roads as possible without interfering with normal road travel or road maintenance activities. Due to the proximity of existing facilities, no temporary use or construction/storage areas are anticipated. If necessary, temporary use or construction/storage areas will be identified on a topographic map included in the approved permit.

Installation: The proposed flow lines will be installed 4-6" above the ground. For portions along existing two-track and primary access roads, lengths of pipe will be strung out in the borrow ditch, welded together, and rolled or dragged into place with heavy equipment. For pipelines that are installed cross-country (not along existing or proposed roads), travel along the lines will be infrequent and for maintenance needs only. No installation activities will be performed during periods when the soil is too wet to adequately support installation equipment. If such equipment creates ruts in excess of three (3) inches deep, the soil will be deemed too wet to adequately support the equipment.

Termination and Final Reclamation: After abandonment of the associated production facilities, the flow lines will be cut and removed, and any incidental surface disturbance reclaimed. Reclamation procedures will follow those outlined in the Castle Peak and Eight Mile Flat Reclamation and Weed Management Plan.

#### **Water Disposal**

After first production, if the production water meets quality guidelines, it will be transported to the Ashley, Monument Butte, Jonah, South Wells Draw and Beluga water injection facilities by company or contract trucks. Subsequently, the produced water is injected into approved Class II wells to enhance Newfield's secondary recovery project. Water not meeting quality criteria, will be disposed at Newfield's Pariette #4 disposal well (Sec. 7, T9S R19E), Federally approved surface disposal facilities or at a State of Utah approved surface disposal facilities.

#### **Additional Surface Stipulations**

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws and regulations, Onshore Oil and Gas Orders, the approved plan of operations and any applicable Notice to Lessees. A copy of these conditions will be furnished to the field representative to ensure compliance.

#### **Details of the On-Site Inspection**

The proposed GMBU V-6-9-17 was on-sited on 2/24/11. The following were present; Tim Eaton (Newfield Production), Christine Cimiluca (Bureau of Land Management), and Suzanne Grayson (Bureau of Land Management).

#### **Hazardous Material Declaration**

Newfield Production Company guarantees that during the drilling and completion of the GMBU V-6-9-17, Newfield will not use, produce, store, transport or dispose 10,000# annually of any of the hazardous chemicals contained in the Environmental Protection Agency's consolidated list of chemicals subject to reporting under Title III Superfund Amendments and Reauthorization Act (SARA) of 1986. Newfield also guarantees that during the drilling and completion of the GMBU V-6-9-17, Newfield will use, produce,

store, transport or dispose less than the threshold planning quantity (T.P.Q.) of any extremely hazardous substances as defined in 40 CFR 355.

A complete copy of the approved APD, if applicable, shall be on location during the construction of the location and drilling activities.

Newfield Production Company or a contractor employed by Newfield Production shall contact the State office at (801) 722-3417, 48 hours prior to construction activities.

13. **LESSEE'S OR OPERATOR'S REPRESENTATIVE AND CERTIFICATION:**

Representative

Name: Tim Eaton  
Address: Newfield Production Company  
Route 3, Box 3630  
Myton, UT 84052  
Telephone: (435) 646-3721

Certification

Please be advised that NEWFIELD PRODUCTION COMPANY is considered to be the operator of well #V-6-9-17, Section 7, Township 9S, Range 17E: Lease UTU-44426 Duchesne County, Utah: and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond coverage is provided by, Federal Bond #WYB000493.

I hereby certify that the proposed drill site and access route have been inspected, and I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and that the work associated with the operations proposed here will be performed by Newfield Production Company and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of the 18 U.S.C. 1001 for the filing of a false statement.

4/14/11  
Date



Mandie Crozier  
Regulatory Specialist  
Newfield Production Company

## 2-M SYSTEM

Blowout Prevention Equipment Systems




EXHIBIT C

**NEWFIELD EXPLORATION COMPANY****WELL PAD INTERFERENCE PLAT****F-8-9-17 (Proposed Well)****V-6-9-17 (Proposed Well)****7-7A-9-17 (Existing Well)****Pad Location: NENE Section 7, T9S, R17E, S.L.B.&M.****TOP HOLE FOOTAGES**

**F-8-9-17 (PROPOSED)**  
743' FNL & 669' FEL

**V-6-9-17 (PROPOSED)**  
722' FNL & 673' FEL

**CENTER OF PATTERN FOOTAGES**

**F-8-9-17 (PROPOSED)**  
1530' FNL & 10' FEL

**V-6-9-17 (PROPOSED)**  
30' FSL & 1380' FEL

**V-6-9-17 (PROPOSED)****F-8-9-17 (PROPOSED)****7A-7-9-17 (EXISTING)**

Pump  
Jack

Existing  
Tanks

Seperator

Future Pit

Edge of  
Existing Pad

Existing  
Anchor  
Typ.

**Note:**

Bearings are based on  
GPS Observations.

**RELATIVE COORDINATES**  
**From Top Hole to Bottom Hole**

| WELL     | NORTH | EAST  |
|----------|-------|-------|
| F-8-9-17 | -986' | 857'  |
| V-6-9-17 | 953'  | -929' |

**RELATIVE COORDINATES**  
**From Top Hole to C.O.P.**

| WELL     | NORTH | EAST  |
|----------|-------|-------|
| F-8-9-17 | -775' | 673'  |
| V-6-9-17 | 739'  | -720' |

**BOTTOM OF HOLE FOOTAGES**

**F-8-9-17 (PROPOSED)**  
1745' FNL & 170' FWL

**V-6-9-17 (PROPOSED)**  
248' FSL & 1585' FEL

**LATITUDE & LONGITUDE**  
**Surface position of Wells (NAD 83)**

| WELL      | LATITUDE       | LONGITUDE       |
|-----------|----------------|-----------------|
| F-8-9-17  | 40° 03' 02.17" | 110° 02' 32.23" |
| V-6-9-17  | 40° 03' 02.37" | 110° 02' 32.29" |
| 7A-7-9-17 | 40° 03' 01.96" | 110° 02' 32.17" |




SURVEYED BY: D.G.      DATE SURVEYED: 06-15-10  
 DRAWN BY: M.W.      DATE DRAWN: 01-20-11  
 SCALE: 1" = 50'      REVISED:

**Tri State**  
Land Surveying, Inc.  
180 NORTH VERNAL AVE. VERNAL, UTAH 84078

(435) 781-2501





**NEWFIELD EXPLORATION COMPANY****CROSS SECTIONS****F-8-9-17 (Proposed Well)****V-6-9-17 (Proposed Well)****7-7A-9-17 (Existing Well)***Pad Location: NENE Section 7, T9S, R17E, S.L.B.&M.*

NOTE:  
UNLESS OTHERWISE NOTED  
CUT SLOPES ARE AT 1:1  
FILL SLOPES ARE AT 1.5:1

**ESTIMATED EARTHWORK QUANTITIES**  
(No Shrink or swell adjustments have been used)  
(Expressed in Cubic Yards)

| ITEM   | CUT | FILL | 6" TOPSOIL                               | EXCESS |
|--------|-----|------|--|--------|
| PAD    | 30  | 0    | Topsoil is<br>not included<br>in Pad Cut | 30     |
| PIT    | 640 | 0    |  | 640    |
| TOTALS | 670 | 0    | 120                                      | 670    |

SURVEYED BY: D.G.

DATE SURVEYED: 07-13-10

DRAWN BY: M.W.

DATE DRAWN: 01-20-11

SCALE: 1" = 50'


REVISED:

**Tri State**  
**Land Surveying, Inc.**

(435) 781-2501

180 NORTH VERNAL AVE. VERNAL, UTAH 84078

**RECEIVED: Apr. 14, 2011**

**NEWFIELD EXPLORATION COMPANY****TYPICAL RIG LAYOUT****F-8-9-17 (Proposed Well)****V-6-9-17 (Proposed Well)****7-7A-9-17 (Existing Well)***Pad Location: NENE Section 7, T9S, R17E, S.L.B.&M.*

|                   |                         |
|-------------------|-------------------------|
| SURVEYED BY: D.G. | DATE SURVEYED: 07-13-10 |
| DRAWN BY: M.W.    | DATE DRAWN: 01-20-11    |
| SCALE: 1" = 50'   | REVISED:                |

**Tri State** (435) 781-2501  
**Land Surveying, Inc.**  
 180 NORTH VERNAL AVE. VERNAL, UTAH 84078



*VIA ELECTRONIC DELIVERY*

April 15, 2011

State of Utah, Division of Oil, Gas and Mining  
ATTN: Diana Mason  
P.O. Box 145801  
Salt Lake City, UT 84114-5801

RE: Directional Drilling  
**GMBU V-6-9-17**  
Greater Monument Butte (Green River) Unit

Surface Hole: T9S-R17E Section 7: NENE (UTU-44426)  
722' FNL 673' FEL

At Target: T9S-R17E Section 6: SWSE (UTU-020252A)  
248' FSL 1585' FEL

Duchesne County, Utah

Dear Ms. Mason:

Pursuant to the filing by Newfield Production Company (NPC) of an Application for Permit to Drill the above referenced well dated 4/14/11, a copy of which is attached, and in accordance with Oil and Gas Conservation Rule R649-3-11, NPC hereby submits this letter as notice of our intention to directionally drill this well.

The surface hole and target locations of this well are both within the boundaries of the Greater Monument Butte Unit (UTU-87538X), of which Newfield certifies that it is the operator. Further, Newfield certifies that all lands within 460 feet of the entire directional well bore are within the Greater Monument Butte Unit.

NPC is permitting this well as a directional well in order to mitigate surface disturbance by utilizing pre-existing roads and pipelines.

NPC hereby requests our application for permit to drill be granted pursuant to R649-3-11. If you have any questions or require further information, please contact the undersigned at 303-383-4197 or by email at [sgillespie@newfield.com](mailto:sgillespie@newfield.com). Your consideration in this matter is greatly appreciated.

Sincerely,  
Newfield Production Company

A handwritten signature in blue ink, appearing to read "Shane Gillespie".

Shane Gillespie  
Land Associate

Form 3160-3  
(August 2007)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## APPLICATION FOR PERMIT TO DRILL OR REENTER


FORM APPROVED  
OMB No. 1004-0137  
Expires July 31, 2010

|   |  |
|---|--|
| 5. Lease Serial No.<br>UTU-44426  |  |
| 6. If Indian, Allottee or Tribe Name<br>NA  |  |
| 7. If Unit or CA Agreement, Name and No.<br>Greater Monument Butte  |  |
| 8. Lease Name and Well No.<br>GMBU V-6-9-17   |  |
| 9. API Well No.   |  |
| 10. Field and Pool, or Exploratory<br>Monument Butte  |  |
| 11. Sec., T. R. M. or Blk. and Survey or Area<br>Sec. 7, T9S R17E   |  |
| 12. County or Parish<br>Duchesne  |  |
| 13. State<br>UT   |  |
| 14. Distance in miles and direction from nearest town or post office*<br>Approximately 14.2 miles southeast of Myton, UT                            |  |
| 15. Distance from proposed* location to nearest property or lease line, ft. Approx. 248' f/lse, NA f/unit (Also to nearest drig. unit line, if any) |  |
| 16. No. of acres in lease<br>394.07   |  |
| 17. Spacing Unit dedicated to this well<br>20 Acres   |  |
| 18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. Approx. 954'                             |  |
| 19. Proposed Depth<br>6,172'  |  |
| 20. BLM/BIA Bond No. on file<br>WYB000493   |  |
| 21. Elevations (Show whether DF, KDB, RT, GL, etc.)<br>5282' GL   |  |
| 22. Approximate date work will start*<br>3/24/11  |  |
| 23. Estimated duration<br>(7) days from SPUD to rig release   |  |

## 24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification   |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM.             |

|  |  |                 |
|--|--|-----------------|
| 25. Signature<br> | Name (Printed Typed)<br>Mandie Crozier | Date<br>4/14/11 |
| Title<br>Regulatory Specialist   |  |                 |
| Approved by (Signature)  | Name (Printed Typed)                   | Date            |
| Title<br>Office  |  |                 |

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.


Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)



# T9S, R17E, S.L.B.&M.



## NEWFIELD EXPLORATION COMPANY

### TRI STATE LAND SURVEYING & CONSULTING


180 NORTH VERNAL AVE. - VERNAL, UTAH 84078  
 (435) 781-2501

|                            |                   |
|----------------------------|-------------------|
| DATE SURVEYED:<br>07-21-10 | SURVEYED BY: D.G. |
| DATE DRAWN:<br>01-20-11    | DRAWN BY: M.W.    |
| REVISED:                   | SCALE: 1" = 1000' |

**V-6-9-17**  
 (Surface Location) NAD 83  
 LATITUDE = 40° 03' 02.37"  
 LONGITUDE = 110° 02' 32.29"

BASIS OF ELEV; Elevations are base on LOCATION: an N.G.S. OPUS Correction.  
 LAT. 40°04'09.56" LONG. 110°00'43.28"  
 (Tristate Aluminum Cap) Elev. 5281.57'





# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Utah State Office  
P.O. Box 45155  
Salt Lake City, Utah 84145-0155

IN REPLY REFER TO:  
3160  
(UT-922)

April 15, 2011

Memorandum

To: Assistant District Manager Minerals, Vernal District  
From: Michael Coulthard, Petroleum Engineer  
Subject: 2011 Plan of Development Greater Monument  
Butte Unit, Duchesne and Uintah Counties,  
Utah.

Pursuant to email between Diana Whitney, Division of Oil, Gas and Mining, and Mickey Coulthard, Utah State Office, Bureau of Land Management, the following wells are planned for calendar year 2011 within the Greater Monument Butte Unit, Duchesne and Uintah Counties, Utah.

| API#                      | WELL NAME      | LOCATION   |
|---------------------------|----------------|--|
| (Proposed PZ GREEN RIVER) |                |  |
| 43-013-50677              | GMBU L-33-8-16 | Sec 33 T08S R16E 2054 FNL 0635 FEL<br>BHL Sec 33 T08S R16E 2371 FSL 1459 FEL |
| 43-013-50678              | GMBU M-33-8-16 | Sec 33 T08S R16E 1699 FSL 1898 FWL<br>BHL Sec 33 T08S R16E 2492 FNL 2395 FEL |
| 43-013-50679              | GMBU N-33-8-16 | Sec 33 T08S R16E 1679 FSL 1891 FWL<br>BHL Sec 33 T08S R16E 2617 FNL 1266 FWL |
| 43-047-51559              | GMBU L-24-8-17 | Sec 24 T08S R17E 0814 FNL 0654 FEL<br>BHL Sec 24 T08S R17E 2484 FSL 1454 FEL |
| 43-047-51560              | GMBU R-24-8-17 | Sec 24 T08S R17E 2007 FSL 2169 FEL<br>BHL Sec 24 T08S R17E 1013 FSL 2512 FEL |
| 43-013-50680              | GMBU N-30-8-17 | Sec 30 T08S R17E 1865 FNL 0649 FWL<br>BHL Sec 30 T08S R17E 2500 FSL 1433 FWL |
| 43-013-50681              | GMBU J-10-9-16 | Sec 11 T09S R16E 0832 FNL 0716 FWL<br>BHL Sec 10 T09S R16E 1618 FNL 0211 FEL |
| 43-013-50683              | GMBU F-14-9-16 | Sec 15 T09S R16E 1861 FNL 0819 FEL<br>BHL Sec 14 T09S R16E 1122 FNL 0241 FWL |

RECEIVED: Apr. 18, 2011

| API #                     | WELL NAME     | LOCATION   |
|---------------------------|---------------|--|
| (Proposed PZ GREEN RIVER) |               |  |
| 43-013-50684              | GMBU V-6-9-17 | Sec 07 T09S R17E 0722 FNL 0673 FEL<br>BHL Sec 06 T09S R17E 0248 FSL 1585 FEL |
| 43-013-50685              | GMBU G-7-9-17 | Sec 07 T09S R17E 1972 FNL 0633 FWL<br>BHL Sec 07 T09S R17E 1011 FNL 1405 FWL |

This office has no objection to permitting the wells at this time.

**Michael L. Coulthard**  
Digitally signed by Michael L. Coulthard  
DN: cn=Michael L. Coulthard, o=Bureau of Land Management,  
ou=Branch of Minerals, email=Michael\_Coulthard@blm.gov, c=US  
Date: 2011.04.15 11:30:49 -06'00'

bcc: File - Greater Monument Butte Unit  
Division of Oil Gas and Mining  
Central Files  
Agr. Sec. Chron  
Fluid Chron

MCoulthard:mc:4-15-11



API Number: 4301350684

Well Name: GMBU V-6-9-17




Township T0.9 . Range R1.7 . Section 07

Meridian: SLBM

Operator: NEWFIELD PRODUCTION COMPANY

Map Prepared:

Map Produced by Diana Mason



## WORKSHEET APPLICATION FOR PERMIT TO DRILL

**APD RECEIVED:** 4/14/2011**API NO. ASSIGNED:** 43013506840000**WELL NAME:** GMBU V-6-9-17**OPERATOR:** NEWFIELD PRODUCTION COMPANY (N2695)**PHONE NUMBER:** 435 646-4825**CONTACT:** Mandie Crozier**PROPOSED LOCATION:** NENE 07 090S 170E**Permit Tech Review:** ☒**SURFACE:** 0722 FNL 0673 FEL**Engineering Review:** ☐**BOTTOM:** 0248 FSL 1585 FEL**Geology Review:** ☒**COUNTY:** DUCHESNE**LATITUDE:** 40.05064**LONGITUDE:** -110.04154**UTM SURF EASTINGS:** 581756.00**NORTHINGS:** 4433608.00**FIELD NAME:** MONUMENT BUTTE**LEASE TYPE:** 1 - Federal**LEASE NUMBER:** UTU-44426**PROPOSED PRODUCING FORMATION(S):** GREEN RIVER**SURFACE OWNER:** 1 - Federal**COALBED METHANE:** NO**RECEIVED AND/OR REVIEWED:**☒ **PLAT**☒ **Bond:** FEDERAL - WYB000493☐ **Potash**☐ **Oil Shale 190-5**☐ **Oil Shale 190-3**☐ **Oil Shale 190-13**☒ **Water Permit:** 437478☐ **RDCC Review:**☐ **Fee Surface Agreement**☐ **Intent to Commingle****Commingle Approved****LOCATION AND SITING:**☐ **R649-2-3.****Unit:** GMBU (GRRV)☐ **R649-3-2. General**☐ **R649-3-3. Exception**☒ **Drilling Unit****Board Cause No:** Cause: 213-11**Effective Date:** 11/30/2009**Siting:** Suspends General Siting☒ **R649-3-11. Directional Drill****Comments:** Presite Completed**Stipulations:**  
4 - Federal Approval - dmason  
15 - Directional - dmason  
27 - Other - bhill**RECEIVED:** Apr. 18, 2011





GARY R. HERBERT  
*Governor*

GREGORY S. BELL  
*Lieutenant Governor*

## State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER  
*Executive Director*

Division of Oil, Gas and Mining

JOHN R. BAZA  
*Division Director*

### Permit To Drill

\*\*\*\*\*

**Well Name:** GMBU V-6-9-17  
**API Well Number:** 43013506840000  
**Lease Number:** UTU-44426  
**Surface Owner:** FEDERAL  
**Approval Date:** 4/18/2011

**Issued to:**

NEWFIELD PRODUCTION COMPANY , Rt 3 Box 3630 , Myton, UT 84052

**Authority:**

Pursuant to Utah Code Ann. §40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause: 213-11. The expected producing formation or pool is the GREEN RIVER Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

**Duration:**

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

**General:**

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

**Conditions of Approval:**

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

Production casing cement shall be brought up to or above the top of the unitized interval for the Greater Monument Butte Unit (Cause No. 213-11).

**Notification Requirements:**

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

- Within 24 hours following the spudding of the well – contact Carol Daniels at 801-538-5284 (please leave a voicemail message if not available)  
OR  
submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website at <http://oilgas.ogm.utah.gov>

**Reporting Requirements:**

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:

- Entity Action Form (Form 6) – due within 5 days of spudding the well
- Monthly Status Report (Form 9) – due by 5th day of the following calendar month
- Requests to Change Plans (Form 9) – due prior to implementation
- Written Notice of Emergency Changes (Form 9) – due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) – due prior to implementation
- Report of Water Encountered (Form 7) – due within 30 days after completion
- Well Completion Report (Form 8) – due within 30 days after completion or plugging

**Approved By:**

A handwritten signature in black ink, appearing to read "J. Rogers", written over a horizontal line.

For John Rogers  
Associate Director, Oil & Gas



# RECEIVED

Form 3160-3  
(August 2007)

APR 18 2011



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**BLM VERNAL UTAH**  
APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED  
OMB No. 1004-0137  
Expires July 31, 2010

|   |  |  |
|---|--|--|
| 1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER  |  | 5. Lease Serial No.<br>UTU-44426                                   |
| 1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone                              |  | 6. If Indian, Allottee or Tribe Name<br>NA                         |
| 2. Name of Operator<br>Newfield Production Company  |  | 7. If Unit or CA Agreement, Name and No.<br>Greater Monument Butte |
| 3a. Address<br>Route #3 Box 3630, Myton UT 84052  |  | 8. Lease Name and Well No.<br>GMBU V-6-9-17                        |
| 3b. Phone No. (include area code)<br>(435) 646-3721   |  | 9. API Well No.<br>43-013-50684                                    |
| 4. Location of Well (Report location clearly and in accordance with any State requirements. *)<br>At surface NE/NE 722' FNL 673' FEL Sec. 7, T9S R17E (UTU-44426)<br>At proposed prod. zone SW/SE 248' FSL 1585' FEL Sec. 6, T9S R17E (UTU-020252A) |  | 10. Field and Pool, or Exploratory<br>Monument Butte               |
| 14. Distance in miles and direction from nearest town or post office*<br>Approximately 14.2 miles southeast of Myton, UT  |  | 11. Sec., T. R. M. or Blk. and Survey or Area<br>Sec. 7, T9S R17E  |
| 15. Distance from proposed* location to nearest property or lease line, ft. Approx. 248' f/lse, NA f/unit (Also to nearest drig. unit line, if any)   | 16. No. of acres in lease<br>394.07                    | 17. Spacing Unit dedicated to this well<br>20 Acres                |
| 18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. Approx. 954'   | 19. Proposed Depth<br>6,172'                           | 20. BLM/BIA Bond No. on file<br>WYB000493                          |
| 21. Elevations (Show whether DF, KDB, RT, GL, etc.)<br>5282' GL   | 22. Approximate date work will start*<br>3rd Qtr. 2011 | 23. Estimated duration<br>(7) days from SPUD to rig release        |
| 24. Attachments   |  |  |

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification
6. Such other site specific information and/or plans as may be required by the BLM.

|  |  |                     |
|--|--|---------------------|
| 25. Signature<br>           | Name (Printed/Typed)<br>Mandie Crozier | Date<br>4/14/11     |
| Title<br>Regulatory Specialist   |  |                     |
| Approved by (Signature)<br> | Name (Printed/Typed)<br>Jerry Kenczka  | Date<br>DEC 15 2011 |
| Title<br>Assistant Field Manager<br>Lands & Mineral Resources  |  |                     |
| Office<br>VERNAL FIELD OFFICE  |  |                     |

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

**CONDITIONS OF APPROVAL ATTACHED**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

NOTICE OF APPROVAL

**UDOGM**

115X50391A

1105 2/11/2011



UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
VERNAL FIELD OFFICE  
170 South 500 East VERNAL, UT 84078 (435) 781-4400



**CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL**

|          |                             |            |                             |
|----------|-----------------------------|------------|-----------------------------|
| Company: | NEWFIELD PRODUCTION COMPANY | Location:  | NENE Sec. 7, T9S, R17E      |
| Well No: | GMBU V-6-9-17               | Lease No:  | UTU-44426                   |
| API No:  | 43-013-50684                | Agreement: | Greater Monument Butte Unit |

**OFFICE NUMBER: (435) 781-4400**

**OFFICE FAX NUMBER: (435) 781-3420**

**A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR  
FIELD REPRESENTATIVE TO INSURE COMPLIANCE**

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. **This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.**

**NOTIFICATION REQUIREMENTS**

|   |  |
|---|--|
| Location Construction<br>(Notify Environmental Scientist)       | - Forty-Eight (48) hours prior to construction of location and access roads.   |
| Location Completion<br>(Notify Environmental Scientist)         | - Prior to moving on the drilling rig.   |
| Spud Notice<br>(Notify Petroleum Engineer)                      | - Twenty-Four (24) hours prior to spudding the well.   |
| Casing String & Cementing<br>(Notify Supv. Petroleum Tech.)     | - Twenty-Four (24) hours prior to running casing and cementing all casing strings to: <a href="mailto:ut_vn_opreport@blm.gov">ut_vn_opreport@blm.gov</a> . |
| BOP & Related Equipment Tests<br>(Notify Supv. Petroleum Tech.) | - Twenty-Four (24) hours prior to initiating pressure tests.   |
| First Production Notice<br>(Notify Petroleum Engineer)          | - Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.             |

**SURFACE USE PROGRAM  
CONDITIONS OF APPROVAL (COAs)**

- After cessation of drilling and completion operations, any visible or measurable layer of oil must be removed from the surface of the reserve pit and the pit kept free of oil.
- Pits must be free of oil and other liquid and solid wastes prior to filling. Pit liners must not be breached (cut) or filled (squeezed) while still containing fluids. The pit liner must be removed to the solids level or treated to prevent its reemergence to the surface or its interference with long-term successful revegetation.

**If construction and drilling is anticipated during any of the following wildlife seasonal or spatial restrictions, a qualified consulting firm biologist must be contacted 2 weeks prior in order to conduct applicable surveys using an accepted protocol prior to any ground disturbing activities.**

- Three raptor nest surveys must be conducted during the nesting season within ½ mile of the project area(s). It is recommended that these surveys be spaced 3 weeks apart, so nesting status and reproductive success can be verified and documented.
- No surface occupancy or use is allowed within ½ mile of golden eagle nests from January 1 through August 31. If during the surveys known nests/habitat is found to be inactive, an exemption may be requested in writing, ~~survey results reviewed and approved by a BLM minerals biologist before granting the exemption.~~ *the Authorized Officer*
- No surface occupancy or use is allowed within 1/4 mile of prairie falcon nests from April 1 to August 31. If during the surveys known nests/habitat is found to be inactive, an exemption may be requested in writing, ~~survey results reviewed and approved by a BLM minerals biologist before granting the exemption.~~ *the Authorized Officer*
- Mountain plover surveys will be conducted to protocol by a professional Environmental Consulting Firm biologist prior to any ground disturbing activities. Reports from survey results must be reviewed by a BLM minerals biologist prior to proceeding with the proposed project. A seasonal restriction for all ground disturbing activities in mountain plover habitat from May 1-June 15 is required.
- Install hospital mufflers where possible to reduce noise impacts to wildlife.

**Reclamation**

- Reclamation will be completed in accordance with the Newfield Exploration Company Castle Peak and Eight Mile Flat Reclamation Plan on file with the Vernal Field Office of the BLM.
- The reclamation seed mix will incorporate low growing grasses, instead of crested wheatgrass, which negatively impacts mountain plover habitat.
- Appropriate erosion control and revegetation measures will be employed. In areas with unstable soils where seeding alone may not adequately control erosion, grading will be used to minimize slopes and water bars will be installed on disturbed slopes. Erosion control efforts will be monitored by Newfield and, if necessary, modifications will be made to control erosion.

### Monitoring and Reporting

- The operator shall submit a Sundry Notice (Form 3160-5) to the BLM Authorized Officer (AO) that designates the proposed site-specific monitoring and reference sites chosen for the location. A description of the proposed sites shall be included, as well as a map showing the locations of the proposed sites.
- The operator shall submit a Sundry Notice (Form 3160-5) to the BLM Authorized Officer (AO) 3 growing seasons after reclamation efforts have occurred evaluating the status of the reclaimed areas in order to determine whether the BLM standards set forth in the Green River District Reclamation Guidelines have been met (30% or greater basal cover).

### Seed Mix (Interim and Final Reclamation)

| Common Name             | Latin Name                    | Pure Live Seed (lbs/acre) | Seed Planting Depth             |
|-------------------------|-------------------------------|---------------------------|---------------------------------|
| Squirreltail grass      | <i>Elymus elymoides</i>       | 2.0                       | $\frac{1}{4}$ - $\frac{1}{2}$ " |
| Needle and thread grass | <i>Hesperostipa comata</i>    | 2.0                       | $\frac{1}{2}$ "                 |
| Siberian Wheatgrass     | <i>Agropyron fragile</i>      | 2.0                       | $\frac{1}{2}$ "                 |
| Shadscale saltbush      | <i>Atriplex confertifolia</i> | 2.0                       | $\frac{1}{2}$ "                 |
| Four-wing saltbush      | <i>Atriplex canescens</i>     | 2.0                       | $\frac{1}{2}$ "                 |
| Gardner's saltbush      | <i>Atriplex gardneri</i>      | 2.0                       | $\frac{1}{2}$ "                 |
| Blue flax (Lewis flax)  | <i>Linum lewisii</i>          | 1.0                       | $\frac{1}{8}$ - $\frac{1}{4}$ " |

- All pounds are pure live seed.
- All seed and mulch will be certified weed free.
- Rates are set for drill seeding; double rate if broadcasting.

### Monitoring and Reporting

- The operator shall submit a Sundry Notice (Form 3160-5) to the BLM Authorized Officer (AO) that designates the proposed site-specific monitoring and reference sites chosen for the location. A description of the proposed sites shall be included, as well as a map showing the locations of the proposed sites.
- The operator shall submit a Sundry Notice (Form 3160-5) to the BLM Authorized Officer (AO) 3 growing seasons after reclamation efforts have occurred evaluating the status of the reclaimed areas in order to determine whether the BLM standards set forth in the Green River District Reclamation Guidelines have been met (30% or greater basal cover).



**DOWNHOLE PROGRAM  
CONDITIONS OF APPROVAL (COAs)**

**SITE SPECIFIC DOWNHOLE COAs:**

- Newfield Production Co. shall comply with all applicable requirements in the SOP (version: "Greater Monument Butte Green River Development Program", June 24, 2008). The operator shall also comply with applicable laws and regulations; with lease terms, Onshore Oil and Gas Orders, NTL's; and with other orders and instructions of the authorized officer.

**All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to.** The following items are emphasized:

**DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS**

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- All requirements listed in Onshore Order #2 III. E. Special Drilling Operations are applicable for air drilling of surface hole.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and **NOT** by the rig pumps. Test shall be reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- **Cement baskets shall not be run on surface casing.**
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB

or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.

- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- **Please submit an electronic copy of all other logs run on this well in LAS format to UT\_VN\_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.**
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

## OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- For information regarding production reporting, contact the Office of Natural Resources Revenue (ONRR) at [www.ONRR.gov](http://www.ONRR.gov).
- Should the well be successfully completed for production, the BLM Vernal Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:
  - Operator name, address, and telephone number.
  - Well name and number.
  - Well location (¼¼, Sec., Twn, Rng, and P.M.).
  - Date well was placed in a producing status (date of first production for which royalty will be paid).
  - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
  - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
  - Unit agreement and/or participating area name and number, if applicable.
  - Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs,

core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field Office Petroleum Engineers will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports shall be submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover equipment shall be removed from a well to be placed in a suspended status without prior approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.



|  |  |   |
|--|--|---|
| <b>STATE OF UTAH</b><br>DEPARTMENT OF NATURAL RESOURCES<br>DIVISION OF OIL, GAS, AND MINING  |  | <b>FORM 9</b>   |
| <b>SUNDRY NOTICES AND REPORTS ON WELLS</b><br><br>Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. |  | <b>5. LEASE DESIGNATION AND SERIAL NUMBER:</b><br>UTU-44426 |
| <b>1. TYPE OF WELL</b><br>Oil Well   |  | <b>6. IF INDIAN, ALLOTTEE OR TRIBE NAME:</b>                |
| <b>2. NAME OF OPERATOR:</b><br>NEWFIELD PRODUCTION COMPANY   |  | <b>7. UNIT or CA AGREEMENT NAME:</b><br>GMBU (GRRV)         |
| <b>3. ADDRESS OF OPERATOR:</b><br>Rt 3 Box 3630 , Myton, UT, 84052   |  | <b>8. WELL NAME and NUMBER:</b><br>GMBU V-6-9-17            |
| <b>PHONE NUMBER:</b><br>435 646-4825 Ext   |  | <b>9. API NUMBER:</b><br>43013506840000                     |
| <b>4. LOCATION OF WELL</b><br><b>FOOTAGES AT SURFACE:</b><br>0722 FNL 0673 FEL<br><b>QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:</b><br>Qtr/Qtr: NENE Section: 07 Township: 09.0S Range: 17.0E Meridian: S  |  | <b>9. FIELD and POOL or WILDCAT:</b><br>MONUMENT BUTTE      |
|  |  | <b>COUNTY:</b><br>DUCHESNE                                  |
|  |  | <b>STATE:</b><br>UTAH                                       |

11.

CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| TYPE OF SUBMISSION   | TYPE OF ACTION  |
|--|---|
| <input checked="" type="checkbox"/> <b>NOTICE OF INTENT</b><br>Approximate date work will start:<br><b>4/18/2012</b> | <div style="display: flex; flex-wrap: wrap;"> <div style="width: 33%;"><input type="checkbox"/> ACIDIZE</div> <div style="width: 33%;"><input type="checkbox"/> ALTER CASING</div> <div style="width: 33%;"><input type="checkbox"/> CASING REPAIR</div> <div style="width: 33%;"><input type="checkbox"/> CHANGE TO PREVIOUS PLANS</div> <div style="width: 33%;"><input type="checkbox"/> CHANGE TUBING</div> <div style="width: 33%;"><input type="checkbox"/> CHANGE WELL NAME</div> <div style="width: 33%;"><input type="checkbox"/> CHANGE WELL STATUS</div> <div style="width: 33%;"><input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS</div> <div style="width: 33%;"><input type="checkbox"/> CONVERT WELL TYPE</div> <div style="width: 33%;"><input type="checkbox"/> DEEPEN</div> <div style="width: 33%;"><input type="checkbox"/> FRACTURE TREAT</div> <div style="width: 33%;"><input type="checkbox"/> NEW CONSTRUCTION</div> <div style="width: 33%;"><input type="checkbox"/> OPERATOR CHANGE</div> <div style="width: 33%;"><input type="checkbox"/> PLUG AND ABANDON</div> <div style="width: 33%;"><input type="checkbox"/> PLUG BACK</div> <div style="width: 33%;"><input type="checkbox"/> PRODUCTION START OR RESUME</div> <div style="width: 33%;"><input type="checkbox"/> RECLAMATION OF WELL SITE</div> <div style="width: 33%;"><input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION</div> <div style="width: 33%;"><input type="checkbox"/> REPERFORATE CURRENT FORMATION</div> <div style="width: 33%;"><input type="checkbox"/> SIDETRACK TO REPAIR WELL</div> <div style="width: 33%;"><input type="checkbox"/> TEMPORARY ABANDON</div> <div style="width: 33%;"><input type="checkbox"/> TUBING REPAIR</div> <div style="width: 33%;"><input type="checkbox"/> VENT OR FLARE</div> <div style="width: 33%;"><input type="checkbox"/> WATER DISPOSAL</div> <div style="width: 33%;"><input type="checkbox"/> WATER SHUTOFF</div> <div style="width: 33%;"><input type="checkbox"/> SI TA STATUS EXTENSION</div> <div style="width: 33%;"><input checked="" type="checkbox"/> APD EXTENSION</div> <div style="width: 33%;"><input type="checkbox"/> WILDCAT WELL DETERMINATION</div> <div style="width: 33%;"><input type="checkbox"/> OTHER</div> </div> |
| <input type="checkbox"/> <b>SUBSEQUENT REPORT</b><br>Date of Work Completion:  |   |
| <input type="checkbox"/> <b>SPUD REPORT</b><br>Date of Spud:   |   |
| <input type="checkbox"/> <b>DRILLING REPORT</b><br>Report Date:  |   |
| OTHER: <input style="width: 100px;" type="text"/>  |   |

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

Newfield proposes to extend the Application for Permit to Drill for one year.

**Approved by the  
 Utah Division of  
 Oil, Gas and Mining**

**Date:** April 09, 2012

**By:**

|  |                                     |                                 |
|--|-------------------------------------|---------------------------------|
| <b>NAME (PLEASE PRINT)</b><br>Mandie Crozier | <b>PHONE NUMBER</b><br>435 646-4825 | <b>TITLE</b><br>Regulatory Tech |
| <b>SIGNATURE</b><br>N/A                      | <b>DATE</b><br>4/4/2012             |                                 |



**The Utah Division of Oil, Gas, and Mining**

- State of Utah
- Department of Natural Resources

**Electronic Permitting System - Sundry Notices**

**Request for Permit Extension Validation Well Number 43013506840000**

**API:** 43013506840000

**Well Name:** GMBU V-6-9-17

**Location:** 0722 FNL 0673 FEL QTR NENE SEC 07 TWP 090S RNG 170E MER S

**Company Permit Issued to:** NEWFIELD PRODUCTION COMPANY

**Date Original Permit Issued:** 4/18/2011

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

- If located on private land, has the ownership changed, if so, has the surface agreement been updated? ☒ Yes ☐ No
- Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? ☐ Yes ☒ No
- Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? ☐ Yes ☒ No
- Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? ☐ Yes ☒ No
- Has the approved source of water for drilling changed? ☐ Yes ☒ No
- Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? ☐ Yes ☒ No
- Is bonding still in place, which covers this proposed well? ☒ Yes ☐ No

**Signature:** Mandie Crozier

**Date:** 4/4/2012

**Title:** Regulatory Tech **Representing:** NEWFIELD PRODUCTION COMPANY

STATE OF UTAH  
DIVISION OF OIL, GAS AND MINING  
ENTITY ACTION FORM -FORM 6

OPERATOR: **NEWFIELD PRODUCTION COMPANY**  
ADDRESS: **RT. 3 BOX 3630**  
**MYTON, UT 84052**


OPERATOR ACCT. NO. **N2695**

| ACTION CODE              | CURRENT ENTITY NO. | NEW ENTITY NO. | API NUMBER | WELL NAME       | WELL LOCATION |    |    |     |          | SPUD DATE | EFFECTIVE DATE |
|--------------------------|--------------------|----------------|------------|-----------------|---------------|----|----|-----|----------|-----------|----------------|
|                          |                    |                |            |                 | QQ            | SC | TP | RG  | COUNTY   |           |                |
| B                        | 99999              | 17400          | 4304751649 | GMBU N-25-8-17  | NWSW          | 25 | 8S | 17E | Uintah   | 4/4/2012  | 4/24/12        |
| WELL 1 COMMENTS:<br>GRRV |                    |                |            |                 |               |    |    |     |          |           |                |
| B                        | 16361              | 17400          | 4304734943 | GMBU 3-14-9-18H | NENW          | 14 | 9S | 18E | Uintah   | 4/4/2012  | 4/24/12        |
| GRRV                     |                    |                |            |                 |               |    |    |     |          |           |                |
| B                        | 99999              | 17400          | 4301350745 | GMBU F-8-9-17   | NENE          | 7  | 9S | 17E | Duchesne | 4/4/2012  | 4/24/12        |
| GRRV                     |                    |                |            |                 |               |    |    |     |          |           |                |
| B                        | 99999              | 17400          | 4301350581 | GMBU R-6-9-17   | SESW          | 6  | 9S | 17E | Duchesne | 4/5/2012  | 4/24/12        |
| GRRV                     |                    |                |            |                 |               |    |    |     |          |           |                |
| B                        | 99999              | 17400          | 4301350684 | GMBU V-6-9-17   | NENE          | 7  | 9S | 17E | Duchesne | 4/4/2012  | 4/24/12        |
| GRRV                     |                    |                |            |                 |               |    |    |     |          |           |                |
|                          |                    |                |            |                 |               |    |    |     |          |           |                |

ACTION CODES (See instructions on back of form)  
A - 1 new entity for new well (single well only)  
B - 1 well to existing entity (group or unit well)  
C - from one existing entity to another existing entity  
D - well from one existing entity to a new entity  
E - other (explain in comments section)

RECEIVED  
APR 18 2012

Div. of Oil, Gas & Mining

  
Signature  
Tabitha Timothy  
Production Clerk  
04/11/12

NOTE: Use COMMENT section to explain why each Action Code was selected.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.**

FORM APPROVED  
OMB No. 1004-0137  
Expires: July 31, 2010

**SUBMIT IN TRIPLICATE - Other Instructions on page 2**

|  |   |
|--|---|
| 1. Type of Well<br><input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other |   |
| 2. Name of Operator<br>NEWFIELD PRODUCTION COMPANY   |   |
| 3a. Address Route 3 Box 3630<br>Myton, UT 84052  | 3b. Phone (include area code)<br>435.646.3721 |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)<br>7 0792 FNL 0673 FEL<br>Section 6 T9S R17E              |   |


|  |
|--|
| 5. Lease Serial No.<br>USA UTU-44426                       |
| 6. If Indian, Allottee or Tribe Name.                      |
| 7. If Unit or CA/Agreement, Name and/or<br>GMBU            |
| 8. Well Name and No.<br>GMBU V-6-9-17                      |
| 9. API Well No.<br>4301350684                              |
| 10. Field and Pool, or Exploratory Area<br>GREATER MB UNIT |
| 11. County or Parish, State<br>DUCHESNE, UT                |

**12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, OR OTHER DATA**

| TYPE OF SUBMISSION                                    | TYPE OF ACTION                               |   |  |   |  |
|---|--|---|--|---|--|
| <input type="checkbox"/> Notice of Intent             | <input type="checkbox"/> Acidize             | <input type="checkbox"/> Deepen           | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off         |  |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Alter Casing        | <input type="checkbox"/> Fracture Treat   | <input type="checkbox"/> Reclamation               | <input type="checkbox"/> Well Integrity         |  |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Casing Repair       | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete                | <input checked="" type="checkbox"/> Other _____ |  |
|   | <input type="checkbox"/> Change Plans        | <input type="checkbox"/> Plug & Abandon   | <input type="checkbox"/> Temporarily Abandon       | Spud Notice _____                               |  |
|   | <input type="checkbox"/> Convert to Injector | <input type="checkbox"/> Plug Back        | <input type="checkbox"/> Water Disposal            | _____   |  |

13. Describe Proposed or Completed Operation: (Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

On 4/4/12 MIRU Ross #29. Spud well @9:00 AM. Drill 340' of 12 1/4" hole with air mist. TIH W/ 8 Jt's 8 5/8" J-55 24# csgn. Set @ 341.07'. On 4/9/12 cement with 170 sks of class "G" w/ 2% CaCL2 + 0.25#/sk Cello- Flake Mixed @ 15.8ppg w/ 1.17ft3/sk yield. Returned 5 barrels cement to pit. WOC.

|  |                    |
|--|--------------------|
| I hereby certify that the foregoing is true and correct (Printed/ Typed)<br>Branden Arnold       | Title              |
| Signature<br> | Date<br>04/11/2012 |

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

|   |              |            |
|---|--------------|------------|
| Approved by _____   | Title _____  | Date _____ |
| Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. | Office _____ |            |

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious and fraudulent statements or representations as to any matter within its jurisdiction  
(Instructions on page 2)

RECEIVED

APR 19 2012

DIV. OF OIL, GAS & MINING



## Casing / Liner Detail

**Well** GMBU V-6-9-17  
**Prospect** Monument Butte  
**Foreman**  
**Run Date:**  
**String Type** Surface, 8.625", 24#, J-55, LTC (Generic)

### - Detail From Top To Bottom -

| Depth  | Length | JTS | Description       | OD    | ID |
|--------|--------|-----|-------------------|-------|----|
| 341.65 | 1.42   | 1   | Well Head         |       |    |
| 343.07 | -2.00  | 1   | Cut Off           |       |    |
| 10.00  | 41.25  | 1   | Shoe Jnt          | 8.625 |    |
| 51.25  | 289.50 | 7   | 8 5/8 Surface Csg | 8.625 |    |
| 340.75 | 0.90   | 1   | Guide Shoe        |       |    |
| 341.07 |        |     | KB                |       |    |

### Cement Detail

| <b>Cement Company:</b> BJ |            |              |       |              |  |
|---------------------------|------------|--------------|-------|--------------|--|
| Slurry                    | # of Sacks | Weight (ppg) | Yield | Volume (ft³) | Description - Slurry Class and Additives |
| Slurry 1                  | 170        | 15.8         | 1.17  | 198.9        | Class G w/ 2% CC                         |

|                                 |      |
|---------------------------------|------|
| Stab-In-Job?                    | No   |
| BHT:                            | 0    |
| Initial Circulation Pressure:   |      |
| Initial Circulation Rate:       |      |
| Final Circulation Pressure:     |      |
| Final Circulation Rate:         |      |
| Displacement Fluid:             |      |
| Displacement Rate:              |      |
| Displacement Volume:            | 18.4 |
| Mud Returns:                    |      |
| Centralizer Type And Placement: |      |

|                               |       |
|-------------------------------|-------|
| Cement To Surface?            | Yes   |
| Est. Top of Cement:           | 0     |
| Plugs Bumped?                 | Yes   |
| Pressure Plugs Bumped:        | 115   |
| Floats Holding?               | No    |
| Casing Stuck On / Off Bottom? | No    |
| Casing Reciprocated?          | No    |
| Casing Rotated?               | No    |
| CIP:                          | 10:22 |
| Casing Wt Prior To Cement:    |       |
| Casing Weight Set On Slips:   |       |

Middle of 1st, 2nd, and 3rd. Total of 3 in csg string.

BLM - Vernal Field Office - Notification Form

Operator Newfield Exploration Rig Name/# NDSI SS #1  
Submitted By Ryan Crum Phone Number 823-7065  
Well Name/Number Greater Mon. Butte V-6-9-17  
Qtr/Qtr NE/NE Section 7 Township 9s Range 17e  
Lease Serial Number UTU-44426  
API Number 43-013-50684

Rig Move Notice – Move drilling rig to new location.

Date/Time 4/29/12 1:00 AM ☐ PM ☒

BOPE

- ☒ Initial BOPE test at surface casing point  
☐ BOPE test at intermediate casing point  
☐ 30 day BOPE test  
☐ Other

Date/Time 4/29/12 4:00 AM ☐ PM ☒

Remarks \_\_\_\_\_

---

RECEIVED

MAY 01 2012

DIV. OF OIL & GAS

BLM - Vernal Field Office - Notification Form

Operator Newfield Exploration Rig Name/# NDSI SS #1  
Submitted By Ryan Crum Phone Number ( 435 ) 823-7065  
Well Name/Number GMB V-6-9-17  
Qtr/Qtr NE/NE Section 7 Township 9s Range 17e  
Lease Serial Number UTU44426  
API Number 43-013-50684

TD Notice – TD is the final drilling depth of hole.

Date/Time 5/3/12      6:00 AM ☐ PM ☒

Casing – Please report time casing run starts, not cementing times.

- ☐ Surface Casing
- ☐ Intermediate Casing
- ☒ Production Casing
- ☐ Liner
- ☐ Other

Date/Time 5/4/12      6:00 AM ☐ PM ☒

**RECEIVED**

**MAY 02 2012**

**DIV. OF OIL, GAS & MINING**

|   |  |   |
|---|--|---|
| <b>STATE OF UTAH</b><br>DEPARTMENT OF NATURAL RESOURCES<br>DIVISION OF OIL, GAS, AND MINING   |  | <b>FORM 9</b>   |
| <b>SUNDRY NOTICES AND REPORTS ON WELLS</b><br><br>Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.  |  | <b>5. LEASE DESIGNATION AND SERIAL NUMBER:</b><br>UTU-44426 |
| <b>1. TYPE OF WELL</b><br>Oil Well  |  | <b>6. IF INDIAN, ALLOTTEE OR TRIBE NAME:</b>                |
| <b>2. NAME OF OPERATOR:</b><br>NEWFIELD PRODUCTION COMPANY  |  | <b>7. UNIT or CA AGREEMENT NAME:</b><br>GMBU (GRRV)         |
| <b>3. ADDRESS OF OPERATOR:</b><br>Rt 3 Box 3630 , Myton, UT, 84052  |  | <b>8. WELL NAME and NUMBER:</b><br>GMBU V-6-9-17            |
| <b>4. LOCATION OF WELL</b><br><b>FOOTAGES AT SURFACE:</b><br>0722 FNL 0673 FEL<br><b>QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:</b><br>Qtr/Qtr: NENE Section: 07 Township: 09.0S Range: 17.0E Meridian: S   |  | <b>9. API NUMBER:</b><br>43013506840000                     |
| <b>9. FIELD and POOL or WILDCAT:</b><br>MONUMENT BUTTE  |  | <b>COUNTY:</b><br>DUCHESNE                                  |
| <b>STATE:</b><br>UTAH   |  |   |
| 11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA   |  |   |
| <b>TYPE OF SUBMISSION</b>   | <b>TYPE OF ACTION</b>  |   |
| <input type="checkbox"/> NOTICE OF INTENT<br>Approximate date work will start:<br><br><input type="checkbox"/> SUBSEQUENT REPORT<br>Date of Work Completion:<br><br><input type="checkbox"/> SPUD REPORT<br>Date of Spud:<br><br><input checked="" type="checkbox"/> DRILLING REPORT<br>Report Date:<br>5/26/2012   | <div style="display: flex; flex-wrap: wrap;"> <div style="width: 33%;"> <input type="checkbox"/> ACIDIZE<br/><br/> <input type="checkbox"/> CHANGE TO PREVIOUS PLANS<br/><br/> <input type="checkbox"/> CHANGE WELL STATUS<br/><br/> <input type="checkbox"/> DEEPEN<br/><br/> <input type="checkbox"/> OPERATOR CHANGE<br/><br/> <input checked="" type="checkbox"/> PRODUCTION START OR RESUME<br/><br/> <input type="checkbox"/> REPERFORATE CURRENT FORMATION<br/><br/> <input type="checkbox"/> TUBING REPAIR<br/><br/> <input type="checkbox"/> WATER SHUTOFF<br/><br/> <input type="checkbox"/> WILDCAT WELL DETERMINATION         </div> <div style="width: 33%;"> <input type="checkbox"/> ALTER CASING<br/><br/> <input type="checkbox"/> CHANGE TUBING<br/><br/> <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS<br/><br/> <input type="checkbox"/> FRACTURE TREAT<br/><br/> <input type="checkbox"/> PLUG AND ABANDON<br/><br/> <input type="checkbox"/> RECLAMATION OF WELL SITE<br/><br/> <input type="checkbox"/> SIDETRACK TO REPAIR WELL<br/><br/> <input type="checkbox"/> VENT OR FLARE<br/><br/> <input type="checkbox"/> SI TA STATUS EXTENSION<br/><br/> <input type="checkbox"/> OTHER         </div> <div style="width: 33%;"> <input type="checkbox"/> CASING REPAIR<br/><br/> <input type="checkbox"/> CHANGE WELL NAME<br/><br/> <input type="checkbox"/> CONVERT WELL TYPE<br/><br/> <input type="checkbox"/> NEW CONSTRUCTION<br/><br/> <input type="checkbox"/> PLUG BACK<br/><br/> <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION<br/><br/> <input type="checkbox"/> TEMPORARY ABANDON<br/><br/> <input type="checkbox"/> WATER DISPOSAL<br/><br/> <input type="checkbox"/> APD EXTENSION<br/><br/>         OTHER: <input style="width: 100%;" type="text"/> </div> </div> |   |
| 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.<br><div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 60%;"> <p>The above well was placed on production on 05/26/2012 at 12:00 hours.</p> </div> <div style="width: 35%; text-align: center;"> <p><b>Accepted by the<br/>Utah Division of<br/>Oil, Gas and Mining</b></p> <p><b>FOR RECORD ONLY</b></p> <p>August 14, 2012</p> </div> </div> |  |   |
| <b>NAME (PLEASE PRINT)</b><br>Jennifer Peatross   | <b>PHONE NUMBER</b><br>435 646-4885  | <b>TITLE</b><br>Production Technician                       |
| <b>SIGNATURE</b><br>N/A   | <b>DATE</b><br>8/13/2012   |   |



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB NO. 1004-0137  
Expires: July 31, 2010

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

| 1a. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Dry <input type="checkbox"/> Other<br>1b. Type of Completion: <input checked="" type="checkbox"/> New Well <input type="checkbox"/> Work Over <input type="checkbox"/> Deepen <input type="checkbox"/> Plug Back <input type="checkbox"/> Diff. Resvr.,<br>Other: _____    |   |                   |                     |                |                      | 5. Lease Serial No.<br><b>UTU-44426</b>   |                       |                   |                                       |
|---|---|-------------------|---------------------|----------------|----------------------|---|-----------------------|-------------------|---------------------------------------|
| 2. Name of Operator<br><b>NEWFIELD EXPLORATION COMPANY</b>  |   |                   |                     |                |                      | 6. If Indian, Allottee or Tribe Name<br><b>NA</b>   |                       |                   |                                       |
| 3. Address<br><b>1401 17TH ST. SUITE 1000 DENVER, CO 80202</b>  |   |                   |                     |                |                      | 7. Unit or CA Agreement Name and No.<br><b>Greater Monument Butte</b>   |                       |                   |                                       |
| 3a. Phone No. (include area code)<br><b>(435) 646-3721</b>  |   |                   |                     |                |                      | 8. Lease Name and Well No.<br><b>GMBU V-6-9-17</b>  |                       |                   |                                       |
| 4. Location of Well (Report location clearly and in accordance with Federal requirements)*<br><br>At surface <b>722' FNL &amp; 673' FEL (NE/NE) SEC. 7, T9S, R17E</b><br><br><b>144' FNL &amp; 1234' (NE/NE) SEC. 7, T9S, R17E (UTU-44426)</b><br><br>At top prod. interval reported below<br><br>At total depth <b>215' FSL &amp; 1600' FEL (SW/SE) SEC. 6, T9S, R17E (UTU-020252A) BHL by HSM</b> |   |                   |                     |                |                      | 9. AFI Well No.<br><b>43-013-50684</b>  |                       |                   |                                       |
| 14. Date Spudded<br><b>04/04/2012</b>   |   |                   |                     |                |                      | 10. Field and Pool or Exploratory<br><b>MONUMENT BUTTE</b>  |                       |                   |                                       |
| 15. Date T.D. Reached<br><b>05/05/2012</b>  |   |                   |                     |                |                      | 11. Sec., T., R., M., on Block and<br>Survey or Area<br><b>SEC. 7, T9S, R17E</b>  |                       |                   |                                       |
| 16. Date Completed <b>05/28/2012</b><br><input type="checkbox"/> D & A <input checked="" type="checkbox"/> Ready to Prod.   |   |                   |                     |                |                      | 12. County or Parish<br><b>DUCHESNE</b>   |                       |                   |                                       |
| 17. Elevations (DF, RKB, RT, GL)*<br><b>5282' GL 5292' KB</b>   |   |                   |                     |                |                      | 13. State<br><b>UT</b>  |                       |                   |                                       |
| 18. Total Depth: MD 6166<br>TVD 6000  |   |                   |                     |                |                      | 19. Plug Back T.D.: MD 6120<br>TVD <b>5956</b>  |                       |                   |                                       |
| 20. Depth Bridge Plug Set: MD<br>TVD  |   |                   |                     |                |                      | 21. Type Electric & Other Mechanical Logs Run (Submit copy of each)<br><b>DUAL IND GRD, SP, COMP. DENSITY, COMP. NEUTRON, GR, CALIPER, CMT BOND</b> |                       |                   |                                       |
| 22. Was well cored? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (Submit analysis)<br>Was DST run? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (Submit report)<br>Directional Survey? <input type="checkbox"/> No <input checked="" type="checkbox"/> Yes (Submit copy)  |   |                   |                     |                |                      |   |                       |                   |                                       |
| 23. Casing and Liner Record (Report all strings set in well)  |   |                   |                     |                |                      |   |                       |                   |                                       |
| Hole Size   | Size/Grade  | Wt. (#/ft.)       | Top (MD)            | Bottom (MD)    | Stage Cementer Depth | No. of Sk. & Type of Cement   | Slurry Vol. (BBL)     | Cement Top*       | Amount Pulled                         |
| 12-1/4"   | 8-5/8" J-55   | 24#               | 0                   | 342'           |                      | 170 CLASS G   |                       |                   |                                       |
| 7-7/8"  | 5-1/2" J-55   | 15.5#             | 0                   | 6139'          |                      | 253 PRIMLITE  |                       | 00'               |                                       |
|   |   |                   |                     |                |                      | 466 50/50 POZ   |                       |                   |                                       |
| 24. Tubing Record   |   |                   |                     |                |                      |   |                       |                   |                                       |
| Size  | Depth Set (MD)  | Packer Depth (MD) | Size                | Depth Set (MD) | Packer Depth (MD)    | Size  | Depth Set (MD)        | Packer Depth (MD) |                                       |
| 2-7/8"  | EOT @ 5702'   | TA @ 5604'        |                     |                |                      |   |                       |                   |                                       |
| 25. Producing Intervals   |   |                   |                     |                |                      |   |                       |                   |                                       |
| Formation   | Top   | Bottom            | Perforated Interval | Size           | No. Holes            | Perf. Status  |                       |                   |                                       |
| A) Green River  | 4182'   | 5642'             | 4182-5642'          | .34"           | 48                   |   |                       |                   |                                       |
| B)  |   |                   |                     |                |                      |   |                       |                   |                                       |
| C)  |   |                   |                     |                |                      |   |                       |                   |                                       |
| D)  |   |                   |                     |                |                      |   |                       |                   |                                       |
| 27. Acid, Fracture, Treatment, Cement Squeeze, etc.   |   |                   |                     |                |                      |   |                       |                   |                                       |
| Depth Interval  | Amount and Type of Material   |                   |                     |                |                      |   |                       |                   |                                       |
| 4182-5642'  | Frac w/ 191411#'s 20/40 sand in 1224 bbls of Lightning 17 fluid in 4 stages |                   |                     |                |                      |   |                       |                   |                                       |
|   |   |                   |                     |                |                      |   |                       |                   |                                       |
|   |   |                   |                     |                |                      |   |                       |                   |                                       |
| 28. Production - Interval A   |   |                   |                     |                |                      |   |                       |                   |                                       |
| Date First Produced   | Test Date   | Hours Tested      | Test Production     | Oil BBL        | Gas MCF              | Water BBL   | Oil Gravity Corr. API | Gas Gravity       | Production Method                     |
| 05/25/12  | 06/04/12  | 24                | →                   | 99             | 68                   | 24  |                       |                   | 2-1/2" x 1-3/4" x 20' x 21' RHAC Pump |
| Choke Size  | Tbg. Press. Flwg. SI  | Csg. Press.       | 24 Hr. Rate         | Oil BBL        | Gas MCF              | Water BBL   | Gas/Oil Ratio         | Well Status       |                                       |
|   |   |                   | →                   |                |                      |   |                       | PRODUCING         |                                       |
| 28a. Production - Interval B  |   |                   |                     |                |                      |   |                       |                   |                                       |
| Date First Produced   | Test Date   | Hours Tested      | Test Production     | Oil BBL        | Gas MCF              | Water BBL   | Oil Gravity Corr. API | Gas Gravity       | Production Method                     |
|   |   |                   | →                   |                |                      |   |                       |                   |                                       |
| Choke Size  | Tbg. Press. Flwg. SI  | Csg. Press.       | 24 Hr. Rate         | Oil BBL        | Gas MCF              | Water BBL   | Gas/Oil Ratio         | Well Status       |                                       |
|   |   |                   | →                   |                |                      |   |                       |                   |                                       |

\*(See instructions and spaces for additional data on page 2)

RECEIVED

AUG 27 2012

DIV. OF OIL, GAS & MINING

## 28b. Production - Interval C

| Date First Produced | Test Date            | Hours Tested | Test Production | Oil BBL | Gas MCF | Water BBL | Oil Gravity Corr. API | Gas Gravity | Production Method |
|---------------------|----------------------|--------------|-----------------|---------|---------|-----------|-----------------------|-------------|-------------------|
|                     |                      |              | →               |         |         |           |                       |             |                   |
| Choke Size          | Tbg. Press. Flwg. SI | Csg. Press.  | 24 Hr. Rate     | Oil BBL | Gas MCF | Water BBL | Gas/Oil Ratio         | Well Status |                   |
|                     |                      |              | →               |         |         |           |                       |             |                   |

## 28c. Production - Interval D

| Date First Produced | Test Date            | Hours Tested | Test Production | Oil BBL | Gas MCF | Water BBL | Oil Gravity Corr. API | Gas Gravity | Production Method |
|---------------------|----------------------|--------------|-----------------|---------|---------|-----------|-----------------------|-------------|-------------------|
|                     |                      |              | →               |         |         |           |                       |             |                   |
| Choke Size          | Tbg. Press. Flwg. SI | Csg. Press.  | 24 Hr. Rate     | Oil BBL | Gas MCF | Water BBL | Gas/Oil Ratio         | Well Status |                   |
|                     |                      |              | →               |         |         |           |                       |             |                   |

29. Disposition of Gas (Solid, used for fuel, vented, etc.)

SOLD AND USED FOR FUEL

## 30. Summary of Porous Zones (Include Aquifers):

Show all important zones of porosity and contents thereof. Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.

## 31. Formation (Log) Markers

## GEOLOGICAL MARKERS

| Formation   | Top   | Bottom | Descriptions, Contents, etc. | Name                                  | Top            |
|-------------|-------|--------|------------------------------|---------------------------------------|----------------|
|             |       |        |                              |                                       | Meas. Depth    |
| GREEN RIVER | 4182' | 5642'  |                              | GARDEN GULCH MRK<br>GARDEN GULCH 1    | 3684'<br>3888' |
|             |       |        |                              | GARDEN GULCH 2<br>POINT 3             | 4009'<br>4279' |
|             |       |        |                              | X MRKR<br>Y MRKR                      | 4546'<br>4582' |
|             |       |        |                              | DOUGALS CREEK MRK<br>BI CARBONATE MRK | 4713'<br>4967' |
|             |       |        |                              | B LIMESTON MRK<br>CASTLE PEAK         | 5090'<br>5574' |
|             |       |        |                              | BASAL CARBONATE<br>WASATCH            | 6022'<br>6144' |

32. Additional remarks (include plugging procedure):

33. Indicate which items have been attached by placing a check in the appropriate boxes:

- ☐ Electrical/Mechanical Logs (1 full set req'd.)     
 ☐ Geologic Report     
 ☐ DST Report     
 ☒ Directional Survey  
☐ Sundry Notice for plugging and cement verification     
 ☐ Core Analysis     
 ☐ Other:

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records (see attached instructions)\*

Name (please print) Chelise StewartTitle Production TechnicianSignature Chelise StewartDate 08/21/2012

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 3)

(Form 3160-4, page 2)

**NEWFIELD**

# **NEWFIELD EXPLORATION**

**USGS Myton SW (UT)**

**SECTION 7 T9S, R17E**

**V-6-9-17**

**Wellbore #1**

**Design: Actual**

## **Standard Survey Report**

**08 May, 2012**



# Payzone Directional Survey Report



**Company:** NEWFIELD EXPLORATION  
**Project:** USGS Myton SW (UT)  
**Site:** SECTION 7 T9S, R17E  
**Well:** V-6-9-17  
**Wellbore:** Wellbore #1  
**Design:** Actual

**Local Co-ordinate Reference:** Well V-6-9-17  
**TVD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**MD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature  
**Database:** EDM 2003.21 Single User Db

**Project** USGS Myton SW (UT), DUCHESNE COUNTY, UT, USA

**Map System:** US State Plane 1983  
**Geo Datum:** North American Datum 1983  
**Map Zone:** Utah Central Zone

**System Datum:** Mean Sea Level

**Site** SECTION 7 T9S, R17E, SEC 7 T9S, R17E

|                              |          |                     |                 |                          |                  |
|------------------------------|----------|---------------------|-----------------|--------------------------|------------------|
| <b>Site Position:</b>        |          | <b>Northing:</b>    | 7,188,503.00 ft | <b>Latitude:</b>         | 40° 2' 42.929 N  |
| <b>From:</b>                 | Lat/Long | <b>Easting:</b>     | 2,046,559.00 ft | <b>Longitude:</b>        | 110° 2' 57.037 W |
| <b>Position Uncertainty:</b> | 0.0 ft   | <b>Slot Radius:</b> | "               | <b>Grid Convergence:</b> | 0.93 °           |

**Well** V-6-9-17, SHL LAT: 40 03 02.37 LONG -110 02 32.29

|                             |              |        |                            |                 |                      |                  |
|-----------------------------|--------------|--------|----------------------------|-----------------|----------------------|------------------|
| <b>Well Position</b>        | <b>+N/-S</b> | 0.0 ft | <b>Northing:</b>           | 7,190,501.10 ft | <b>Latitude:</b>     | 40° 3' 2.370 N   |
|                             | <b>+E/-W</b> | 0.0 ft | <b>Easting:</b>            | 2,048,451.09 ft | <b>Longitude:</b>    | 110° 2' 32.290 W |
| <b>Position Uncertainty</b> |              | 0.0 ft | <b>Wellhead Elevation:</b> | 5,292.0 ft      | <b>Ground Level:</b> | 5,282.0 ft       |

**Wellbore** Wellbore #1

|                  |                   |                    |                        |                      |                            |
|------------------|-------------------|--------------------|------------------------|----------------------|----------------------------|
| <b>Magnetics</b> | <b>Model Name</b> | <b>Sample Date</b> | <b>Declination (°)</b> | <b>Dip Angle (°)</b> | <b>Field Strength (nT)</b> |
|                  | IGRF2010          | 1/19/2011          | 11.36                  | 65.81                | 52,318                     |

**Design** Actual

**Audit Notes:**

**Version:** 1.0 **Phase:** ACTUAL **Tie On Depth:** 0.0

|                          |                         |                   |                   |                      |
|--------------------------|-------------------------|-------------------|-------------------|----------------------|
| <b>Vertical Section:</b> | <b>Depth From (TVD)</b> | <b>+N/-S (ft)</b> | <b>+E/-W (ft)</b> | <b>Direction (°)</b> |
|                          | 0.0                     | 0.0               | 0.0               | 315.73               |

**Survey Program** Date 5/8/2012

|                  |                |                          |                  |                    |
|------------------|----------------|--------------------------|------------------|--------------------|
| <b>From (ft)</b> | <b>To (ft)</b> | <b>Survey (Wellbore)</b> | <b>Tool Name</b> | <b>Description</b> |
| 346.0            | 6,166.0        | Survey #1 (Wellbore #1)  | MWD              | MWD - Standard     |

**Survey**

| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Vertical Section (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|-----------------------|----------------------|---------------------|
| 0.0                 | 0.00            | 0.00        | 0.0                 | 0.0        | 0.0        | 0.0                   | 0.00                  | 0.00                 | 0.00                |
| 346.0               | 1.20            | 345.70      | 346.0               | 3.5        | -0.9       | 3.1                   | 0.35                  | 0.35                 | 0.00                |
| 377.0               | 1.20            | 346.60      | 377.0               | 4.1        | -1.1       | 3.7                   | 0.06                  | 0.00                 | 2.90                |
| 407.0               | 1.50            | 339.60      | 407.0               | 4.8        | -1.3       | 4.3                   | 1.14                  | 1.00                 | -23.33              |
| 438.0               | 2.00            | 335.00      | 437.9               | 5.7        | -1.6       | 5.2                   | 1.67                  | 1.61                 | -14.84              |
| 469.0               | 2.50            | 331.20      | 468.9               | 6.8        | -2.2       | 6.4                   | 1.68                  | 1.61                 | -12.26              |
| 499.0               | 2.80            | 330.60      | 498.9               | 8.0        | -2.9       | 7.7                   | 1.00                  | 1.00                 | -2.00               |
| 530.0               | 3.00            | 334.00      | 529.8               | 9.4        | -3.6       | 9.2                   | 0.85                  | 0.65                 | 10.97               |
| 560.0               | 3.20            | 335.80      | 559.8               | 10.8       | -4.3       | 10.7                  | 0.74                  | 0.67                 | 6.00                |
| 590.0               | 3.60            | 333.10      | 589.8               | 12.4       | -5.0       | 12.4                  | 1.44                  | 1.33                 | -9.00               |
| 620.0               | 4.10            | 333.90      | 619.7               | 14.2       | -5.9       | 14.3                  | 1.68                  | 1.67                 | 2.67                |
| 651.0               | 4.70            | 334.50      | 650.6               | 16.4       | -7.0       | 16.6                  | 1.94                  | 1.94                 | 1.94                |
| 682.0               | 5.00            | 331.40      | 681.5               | 18.7       | -8.2       | 19.1                  | 1.28                  | 0.97                 | -10.00              |





# Payzone Directional Survey Report



**Company:** NEWFIELD EXPLORATION  
**Project:** USGS Myton SW (UT)  
**Site:** SECTION 7 T9S, R17E  
**Well:** V-6-9-17  
**Wellbore:** Wellbore #1  
**Design:** Actual

**Local Co-ordinate Reference:** Well V-6-9-17  
**TVD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**MD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature  
**Database:** EDM 2003.21 Single User Db

## Survey

| Measured<br>Depth<br>(ft) | Inclination<br>(°) | Azimuth<br>(°) | Vertical<br>Depth<br>(ft) | +N/-S<br>(ft) | +E/-W<br>(ft) | Vertical<br>Section<br>(ft) | Dogleg<br>Rate<br>(°/100ft) | Build<br>Rate<br>(°/100ft) | Turn<br>Rate<br>(°/100ft) |
|---------------------------|--------------------|----------------|---------------------------|---------------|---------------|-----------------------------|-----------------------------|----------------------------|---------------------------|
| 713.0                     | 5.10               | 328.20         | 712.4                     | 21.1          | -9.5          | 21.8                        | 0.96                        | 0.32                       | -10.32                    |
| 744.0                     | 5.30               | 325.60         | 743.2                     | 23.4          | -11.1         | 24.5                        | 1.00                        | 0.65                       | -8.39                     |
| 774.0                     | 5.20               | 319.10         | 773.1                     | 25.6          | -12.7         | 27.2                        | 2.01                        | -0.33                      | -21.67                    |
| 805.0                     | 5.40               | 315.30         | 804.0                     | 27.7          | -14.7         | 30.1                        | 1.30                        | 0.65                       | -12.26                    |
| 835.0                     | 5.50               | 314.20         | 833.8                     | 29.7          | -16.7         | 32.9                        | 0.48                        | 0.33                       | -3.67                     |
| 866.0                     | 5.40               | 314.00         | 864.7                     | 31.8          | -18.8         | 35.9                        | 0.33                        | -0.32                      | -0.65                     |
| 896.0                     | 5.40               | 315.60         | 894.6                     | 33.7          | -20.8         | 38.7                        | 0.50                        | 0.00                       | 5.33                      |
| 926.0                     | 5.40               | 316.50         | 924.4                     | 35.8          | -22.8         | 41.5                        | 0.28                        | 0.00                       | 3.00                      |
| 957.0                     | 5.50               | 316.20         | 955.3                     | 37.9          | -24.8         | 44.5                        | 0.34                        | 0.32                       | -0.97                     |
| 987.0                     | 5.60               | 315.40         | 985.2                     | 40.0          | -26.9         | 47.4                        | 0.42                        | 0.33                       | -2.67                     |
| 1,017.0                   | 5.90               | 315.80         | 1,015.0                   | 42.1          | -29.0         | 50.4                        | 1.01                        | 1.00                       | 1.33                      |
| 1,061.0                   | 6.10               | 315.70         | 1,058.8                   | 45.4          | -32.2         | 55.0                        | 0.46                        | 0.45                       | -0.23                     |
| 1,105.0                   | 6.90               | 317.70         | 1,102.5                   | 49.1          | -35.6         | 60.0                        | 1.89                        | 1.82                       | 4.55                      |
| 1,149.0                   | 7.30               | 317.90         | 1,146.1                   | 53.1          | -39.2         | 65.4                        | 0.91                        | 0.91                       | 0.45                      |
| 1,193.0                   | 7.70               | 314.50         | 1,189.8                   | 57.2          | -43.2         | 71.1                        | 1.36                        | 0.91                       | -7.73                     |
| 1,237.0                   | 8.20               | 313.20         | 1,233.3                   | 61.4          | -47.6         | 77.2                        | 1.21                        | 1.14                       | -2.95                     |
| 1,281.0                   | 8.70               | 315.50         | 1,276.9                   | 66.0          | -52.2         | 83.7                        | 1.37                        | 1.14                       | 5.23                      |
| 1,325.0                   | 9.30               | 315.80         | 1,320.3                   | 70.9          | -57.0         | 90.6                        | 1.37                        | 1.36                       | 0.68                      |
| 1,369.0                   | 9.70               | 314.60         | 1,363.7                   | 76.0          | -62.1         | 97.8                        | 1.01                        | 0.91                       | -2.73                     |
| 1,413.0                   | 10.10              | 314.60         | 1,407.1                   | 81.3          | -67.5         | 105.4                       | 0.91                        | 0.91                       | 0.00                      |
| 1,457.0                   | 10.90              | 313.80         | 1,450.3                   | 86.9          | -73.3         | 113.4                       | 1.85                        | 1.82                       | -1.82                     |
| 1,501.0                   | 11.30              | 310.30         | 1,493.5                   | 92.6          | -79.6         | 121.9                       | 1.78                        | 0.91                       | -7.95                     |
| 1,545.0                   | 11.10              | 308.00         | 1,536.7                   | 98.0          | -86.2         | 130.3                       | 1.11                        | -0.45                      | -5.23                     |
| 1,589.0                   | 11.20              | 308.10         | 1,579.8                   | 103.2         | -92.9         | 138.8                       | 0.23                        | 0.23                       | 0.23                      |
| 1,633.0                   | 11.60              | 306.50         | 1,623.0                   | 108.5         | -99.8         | 147.4                       | 1.16                        | 0.91                       | -3.64                     |
| 1,677.0                   | 11.90              | 305.00         | 1,666.0                   | 113.7         | -107.1        | 156.2                       | 0.97                        | 0.68                       | -3.41                     |
| 1,721.0                   | 12.20              | 303.80         | 1,709.1                   | 118.9         | -114.7        | 165.2                       | 0.89                        | 0.68                       | -2.73                     |
| 1,765.0                   | 12.30              | 303.20         | 1,752.1                   | 124.1         | -122.5        | 174.3                       | 0.37                        | 0.23                       | -1.36                     |
| 1,809.0                   | 12.90              | 303.70         | 1,795.0                   | 129.4         | -130.5        | 183.7                       | 1.39                        | 1.36                       | 1.14                      |
| 1,853.0                   | 13.40              | 307.30         | 1,837.9                   | 135.2         | -138.6        | 193.6                       | 2.18                        | 1.14                       | 8.18                      |
| 1,897.0                   | 14.10              | 308.50         | 1,880.6                   | 141.6         | -146.9        | 203.9                       | 1.72                        | 1.59                       | 2.73                      |
| 1,941.0                   | 14.90              | 310.00         | 1,923.2                   | 148.6         | -155.4        | 214.9                       | 2.01                        | 1.82                       | 3.41                      |
| 1,985.0                   | 15.70              | 310.40         | 1,965.6                   | 156.1         | -164.2        | 226.4                       | 1.83                        | 1.82                       | 0.91                      |
| 2,029.0                   | 16.00              | 312.30         | 2,008.0                   | 164.0         | -173.3        | 238.4                       | 1.36                        | 0.68                       | 4.32                      |
| 2,073.0                   | 15.80              | 314.50         | 2,050.3                   | 172.3         | -182.0        | 250.4                       | 1.44                        | -0.45                      | 5.00                      |
| 2,117.0                   | 15.90              | 314.50         | 2,092.6                   | 180.7         | -190.6        | 262.5                       | 0.23                        | 0.23                       | 0.00                      |
| 2,161.0                   | 16.30              | 316.10         | 2,134.9                   | 189.4         | -199.2        | 274.7                       | 1.36                        | 0.91                       | 3.64                      |
| 2,205.0                   | 16.80              | 317.50         | 2,177.1                   | 198.5         | -207.8        | 287.2                       | 1.45                        | 1.14                       | 3.18                      |
| 2,249.0                   | 16.70              | 316.90         | 2,219.2                   | 207.8         | -216.4        | 299.9                       | 0.45                        | -0.23                      | -1.36                     |
| 2,293.0                   | 16.60              | 316.50         | 2,261.3                   | 217.0         | -225.0        | 312.5                       | 0.35                        | -0.23                      | -0.91                     |
| 2,337.0                   | 16.40              | 316.70         | 2,303.5                   | 226.1         | -233.6        | 325.0                       | 0.47                        | -0.45                      | 0.45                      |
| 2,381.0                   | 16.00              | 317.70         | 2,345.8                   | 235.1         | -241.9        | 337.2                       | 1.11                        | -0.91                      | 2.27                      |
| 2,425.0                   | 15.90              | 316.80         | 2,388.1                   | 244.0         | -250.1        | 349.3                       | 0.61                        | -0.23                      | -2.05                     |
| 2,469.0                   | 15.50              | 316.90         | 2,430.5                   | 252.7         | -258.3        | 361.2                       | 0.91                        | -0.91                      | 0.23                      |
| 2,513.0                   | 14.80              | 318.40         | 2,472.9                   | 261.2         | -266.0        | 372.7                       | 1.82                        | -1.59                      | 3.41                      |
| 2,557.0                   | 14.80              | 319.30         | 2,515.5                   | 269.6         | -273.4        | 383.9                       | 0.52                        | 0.00                       | 2.05                      |
| 2,601.0                   | 15.80              | 320.90         | 2,557.9                   | 278.5         | -280.9        | 395.5                       | 2.47                        | 2.27                       | 3.64                      |
| 2,645.0                   | 16.80              | 323.70         | 2,600.1                   | 288.3         | -288.4        | 407.8                       | 2.89                        | 2.27                       | 6.36                      |
| 2,689.0                   | 17.70              | 324.00         | 2,642.2                   | 298.8         | -296.1        | 420.7                       | 2.06                        | 2.05                       | 0.68                      |
| 2,733.0                   | 18.00              | 324.60         | 2,684.0                   | 309.8         | -304.0        | 434.0                       | 0.80                        | 0.68                       | 1.36                      |
| 2,777.0                   | 17.60              | 323.70         | 2,725.9                   | 320.7         | -311.9        | 447.3                       | 1.10                        | -0.91                      | -2.05                     |
| 2,821.0                   | 17.90              | 323.20         | 2,767.8                   | 331.5         | -319.9        | 460.6                       | 0.76                        | 0.68                       | -1.14                     |
| 2,865.0                   | 17.60              | 323.50         | 2,809.7                   | 342.2         | -327.9        | 473.9                       | 0.71                        | -0.68                      | 0.68                      |
| 2,909.0                   | 16.20              | 321.60         | 2,851.8                   | 352.4         | -335.6        | 486.6                       | 3.42                        | -3.18                      | -4.32                     |



Company: NEWFIELD EXPLORATION  
 Project: USGS Myton SW (UT)  
 Site: SECTION 7 T9S, R17E  
 Well: V-6-9-17  
 Wellbore: Wellbore #1  
 Design: Actual

Local Co-ordinate Reference: Well V-6-9-17  
 TVD Reference: V-6-9-17 @ 5292.0ft (NDSI SS #1)  
 MD Reference: V-6-9-17 @ 5292.0ft (NDSI SS #1)  
 North Reference: True  
 Survey Calculation Method: Minimum Curvature  
 Database: EDM 2003.21 Single User Db

## Survey

| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Vertical Section (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|-----------------------|----------------------|---------------------|
| 2,953.0             | 16.00           | 320.60      | 2,894.1             | 361.9      | -343.3     | 498.8                 | 0.78                  | -0.45                | -2.27               |
| 2,997.0             | 16.30           | 319.80      | 2,936.4             | 371.3      | -351.1     | 511.0                 | 0.85                  | 0.68                 | -1.82               |
| 3,041.0             | 14.80           | 318.20      | 2,978.8             | 380.2      | -358.9     | 522.7                 | 3.55                  | -3.41                | -3.64               |
| 3,085.0             | 13.50           | 316.70      | 3,021.4             | 388.1      | -366.1     | 533.5                 | 3.07                  | -2.95                | -3.41               |
| 3,129.0             | 13.40           | 316.20      | 3,064.2             | 395.5      | -373.2     | 543.7                 | 0.35                  | -0.23                | -1.14               |
| 3,173.0             | 14.20           | 317.30      | 3,107.0             | 403.2      | -380.4     | 554.2                 | 1.91                  | 1.82                 | 2.50                |
| 3,217.0             | 14.50           | 317.70      | 3,149.6             | 411.2      | -387.7     | 565.1                 | 0.72                  | 0.68                 | 0.91                |
| 3,261.0             | 14.40           | 316.10      | 3,192.2             | 419.2      | -395.2     | 576.1                 | 0.94                  | -0.23                | -3.64               |
| 3,305.0             | 14.50           | 314.10      | 3,234.8             | 427.0      | -403.0     | 587.1                 | 1.16                  | 0.23                 | -4.55               |
| 3,349.0             | 14.50           | 312.60      | 3,277.4             | 434.6      | -411.0     | 598.1                 | 0.85                  | 0.00                 | -3.41               |
| 3,393.0             | 15.00           | 314.30      | 3,319.9             | 442.3      | -419.1     | 609.3                 | 1.50                  | 1.14                 | 3.86                |
| 3,437.0             | 15.60           | 314.80      | 3,362.4             | 450.4      | -427.4     | 620.9                 | 1.40                  | 1.36                 | 1.14                |
| 3,481.0             | 15.60           | 314.00      | 3,404.8             | 458.7      | -435.8     | 632.7                 | 0.49                  | 0.00                 | -1.82               |
| 3,525.0             | 15.40           | 313.70      | 3,447.2             | 466.9      | -444.3     | 644.5                 | 0.49                  | -0.45                | -0.68               |
| 3,569.0             | 15.30           | 312.80      | 3,489.6             | 474.8      | -452.8     | 656.1                 | 0.59                  | -0.23                | -2.05               |
| 3,613.0             | 15.30           | 312.50      | 3,532.0             | 482.7      | -461.4     | 667.7                 | 0.18                  | 0.00                 | -0.68               |
| 3,657.0             | 15.90           | 313.40      | 3,574.4             | 490.8      | -470.0     | 679.5                 | 1.47                  | 1.36                 | 2.05                |
| 3,701.0             | 15.60           | 314.60      | 3,616.8             | 499.1      | -478.6     | 691.4                 | 1.01                  | -0.68                | 2.73                |
| 3,745.0             | 14.80           | 313.00      | 3,659.2             | 507.1      | -486.9     | 703.0                 | 2.05                  | -1.82                | -3.64               |
| 3,789.0             | 14.90           | 312.20      | 3,701.8             | 514.7      | -495.2     | 714.2                 | 0.52                  | 0.23                 | -1.82               |
| 3,833.0             | 14.70           | 312.20      | 3,744.3             | 522.2      | -503.6     | 725.5                 | 0.45                  | -0.45                | 0.00                |
| 3,877.0             | 14.70           | 312.60      | 3,786.9             | 529.8      | -511.8     | 736.6                 | 0.23                  | 0.00                 | 0.91                |
| 3,921.0             | 15.00           | 312.20      | 3,829.4             | 537.4      | -520.1     | 747.9                 | 0.72                  | 0.68                 | -0.91               |
| 3,965.0             | 15.10           | 312.60      | 3,871.9             | 545.1      | -528.6     | 759.3                 | 0.33                  | 0.23                 | 0.91                |
| 4,009.0             | 14.90           | 314.80      | 3,914.4             | 552.9      | -536.8     | 770.6                 | 1.37                  | -0.45                | 5.00                |
| 4,053.0             | 15.10           | 316.40      | 3,956.9             | 561.1      | -544.8     | 782.0                 | 1.05                  | 0.45                 | 3.64                |
| 4,097.0             | 15.30           | 316.60      | 3,999.3             | 569.4      | -552.7     | 793.6                 | 0.47                  | 0.45                 | 0.45                |
| 4,141.0             | 15.30           | 316.90      | 4,041.8             | 577.9      | -560.7     | 805.2                 | 0.18                  | 0.00                 | 0.68                |
| 4,185.0             | 15.30           | 316.80      | 4,084.2             | 586.4      | -568.6     | 816.8                 | 0.06                  | 0.00                 | -0.23               |
| 4,229.0             | 15.20           | 317.20      | 4,126.7             | 594.8      | -576.5     | 828.3                 | 0.33                  | -0.23                | 0.91                |
| 4,273.0             | 15.70           | 317.40      | 4,169.1             | 603.4      | -584.4     | 840.1                 | 1.14                  | 1.14                 | 0.45                |
| 4,317.0             | 15.90           | 318.20      | 4,211.4             | 612.3      | -592.5     | 852.0                 | 0.67                  | 0.45                 | 1.82                |
| 4,361.0             | 15.70           | 318.20      | 4,253.8             | 621.3      | -600.5     | 864.0                 | 0.45                  | -0.45                | 0.00                |
| 4,405.0             | 15.10           | 317.60      | 4,296.2             | 629.9      | -608.3     | 875.7                 | 1.41                  | -1.36                | -1.36               |
| 4,449.0             | 15.20           | 318.10      | 4,338.6             | 638.5      | -616.0     | 887.2                 | 0.37                  | 0.23                 | 1.14                |
| 4,493.0             | 15.80           | 317.00      | 4,381.0             | 647.1      | -624.0     | 898.9                 | 1.52                  | 1.36                 | -2.50               |
| 4,537.0             | 15.90           | 315.40      | 4,423.4             | 655.8      | -632.3     | 910.9                 | 1.02                  | 0.23                 | -3.64               |
| 4,581.0             | 15.80           | 316.50      | 4,465.7             | 664.4      | -640.6     | 923.0                 | 0.72                  | -0.23                | 2.50                |
| 4,625.0             | 15.40           | 316.60      | 4,508.1             | 673.0      | -648.8     | 934.8                 | 0.91                  | -0.91                | 0.23                |
| 4,669.0             | 15.50           | 317.40      | 4,550.5             | 681.6      | -656.8     | 946.5                 | 0.54                  | 0.23                 | 1.82                |
| 4,713.0             | 14.90           | 317.90      | 4,593.0             | 690.1      | -664.5     | 958.0                 | 1.40                  | -1.36                | 1.14                |
| 4,757.0             | 14.30           | 316.70      | 4,635.5             | 698.3      | -672.1     | 969.1                 | 1.53                  | -1.36                | -2.73               |
| 4,801.0             | 13.80           | 315.50      | 4,678.2             | 706.0      | -679.5     | 979.8                 | 1.32                  | -1.14                | -2.73               |
| 4,845.0             | 13.60           | 314.40      | 4,721.0             | 713.3      | -686.8     | 990.2                 | 0.75                  | -0.45                | -2.50               |
| 4,889.0             | 13.40           | 313.40      | 4,763.7             | 720.5      | -694.2     | 1,000.5               | 0.70                  | -0.45                | -2.27               |
| 4,933.0             | 13.40           | 312.10      | 4,806.6             | 727.4      | -701.7     | 1,010.7               | 0.68                  | 0.00                 | -2.95               |
| 4,977.0             | 13.40           | 312.30      | 4,849.4             | 734.2      | -709.3     | 1,020.9               | 0.11                  | 0.00                 | 0.45                |
| 5,021.0             | 13.20           | 312.20      | 4,892.2             | 741.0      | -716.8     | 1,031.0               | 0.46                  | -0.45                | -0.23               |
| 5,028.8             | 13.25           | 312.18      | 4,899.8             | 742.2      | -718.1     | 1,032.7               | 0.68                  | 0.68                 | -0.23               |
| <b>V-6-9-17 TGT</b> |                 |             |                     |            |            |                       |                       |                      |                     |
| 5,065.0             | 13.50           | 312.10      | 4,935.0             | 747.9      | -724.3     | 1,041.1               | 0.68                  | 0.68                 | -0.23               |
| 5,109.0             | 13.60           | 310.70      | 4,977.8             | 754.7      | -732.0     | 1,051.4               | 0.78                  | 0.23                 | -3.18               |
| 5,153.0             | 14.00           | 312.50      | 5,020.5             | 761.6      | -739.9     | 1,061.8               | 1.33                  | 0.91                 | 4.09                |
| 5,197.0             | 14.30           | 313.40      | 5,063.2             | 769.0      | -747.8     | 1,072.6               | 0.85                  | 0.68                 | 2.05                |



**Company:** NEWFIELD EXPLORATION  
**Project:** USGS Myton SW (UT)  
**Site:** SECTION 7 T9S, R17E  
**Well:** V-6-9-17  
**Wellbore:** Wellbore #1  
**Design:** Actual

**Local Co-ordinate Reference:** Well V-6-9-17  
**TVD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**MD Reference:** V-6-9-17 @ 5292.0ft (NDSI SS #1)  
**North Reference:** True  
**Survey Calculation Method:** Minimum Curvature  
**Database:** EDM 2003.21 Single User Db

## Survey

| Measured Depth (ft) | Inclination (°) | Azimuth (°) | Vertical Depth (ft) | +N/-S (ft) | +E/-W (ft) | Vertical Section (ft) | Dogleg Rate (°/100ft) | Build Rate (°/100ft) | Turn Rate (°/100ft) |
|---------------------|-----------------|-------------|---------------------|------------|------------|-----------------------|-----------------------|----------------------|---------------------|
| 5,241.0             | 14.90           | 312.80      | 5,105.7             | 776.5      | -755.8     | 1,083.7               | 1.41                  | 1.36                 | -1.36               |
| 5,285.0             | 15.00           | 312.90      | 5,148.2             | 784.3      | -764.2     | 1,095.0               | 0.23                  | 0.23                 | 0.23                |
| 5,329.0             | 15.00           | 314.00      | 5,190.7             | 792.1      | -772.4     | 1,106.4               | 0.65                  | 0.00                 | 2.50                |
| 5,373.0             | 15.80           | 315.20      | 5,233.2             | 800.3      | -780.8     | 1,118.1               | 1.96                  | 1.82                 | 2.73                |
| 5,417.0             | 16.00           | 315.40      | 5,275.5             | 808.9      | -789.2     | 1,130.1               | 0.47                  | 0.45                 | 0.45                |
| 5,461.0             | 15.60           | 314.80      | 5,317.8             | 817.4      | -797.7     | 1,142.1               | 0.98                  | -0.91                | -1.36               |
| 5,505.0             | 14.80           | 312.90      | 5,360.3             | 825.3      | -806.0     | 1,153.6               | 2.14                  | -1.82                | -4.32               |
| 5,549.0             | 14.30           | 312.90      | 5,402.9             | 832.9      | -814.1     | 1,164.7               | 1.14                  | -1.14                | 0.00                |
| 5,593.0             | 14.20           | 313.60      | 5,445.5             | 840.3      | -822.0     | 1,175.5               | 0.45                  | -0.23                | 1.59                |
| 5,637.0             | 15.00           | 313.80      | 5,488.1             | 848.0      | -830.0     | 1,186.6               | 1.82                  | 1.82                 | 0.45                |
| 5,681.0             | 14.90           | 313.60      | 5,530.6             | 855.8      | -838.2     | 1,197.9               | 0.26                  | -0.23                | -0.45               |
| 5,725.0             | 14.20           | 313.10      | 5,573.2             | 863.4      | -846.3     | 1,209.0               | 1.62                  | -1.59                | -1.14               |
| 5,769.0             | 14.80           | 312.50      | 5,615.8             | 870.9      | -854.3     | 1,220.0               | 1.41                  | 1.36                 | -1.36               |
| 5,813.0             | 15.30           | 311.80      | 5,658.3             | 878.5      | -862.8     | 1,231.4               | 1.21                  | 1.14                 | -1.59               |
| 5,857.0             | 15.50           | 311.20      | 5,700.7             | 886.3      | -871.6     | 1,243.0               | 0.58                  | 0.45                 | -1.36               |
| 5,901.0             | 15.60           | 312.10      | 5,743.1             | 894.1      | -880.4     | 1,254.8               | 0.59                  | 0.23                 | 2.05                |
| 5,945.0             | 15.50           | 312.30      | 5,785.5             | 902.0      | -889.1     | 1,266.5               | 0.26                  | -0.23                | 0.45                |
| 5,989.0             | 14.80           | 312.80      | 5,828.0             | 909.8      | -897.6     | 1,278.0               | 1.62                  | -1.59                | 1.14                |
| 6,033.0             | 13.90           | 312.40      | 5,870.6             | 917.2      | -905.6     | 1,288.9               | 2.06                  | -2.05                | -0.91               |
| 6,077.0             | 12.70           | 312.10      | 5,913.4             | 924.0      | -913.1     | 1,299.0               | 2.73                  | -2.73                | -0.68               |
| 6,112.0             | 12.10           | 311.30      | 5,947.6             | 929.0      | -918.7     | 1,306.5               | 1.78                  | -1.71                | -2.29               |
| 6,166.0             | 12.10           | 311.30      | 6,000.4             | 936.5      | -927.2     | 1,317.8               | 0.00                  | 0.00                 | 0.00                |

Checked By: \_\_\_\_\_ Approved By: \_\_\_\_\_ Date: \_\_\_\_\_





Project: USGS Myton SW (UT)  
 Site: SECTION 7 T9S, R17E  
 Well: V-6-9-17  
 Wellbore: Wellbore #1  
 Design: Actual



Azimuths to True North  
 Magnetic North: 11.36°

Magnetic Field  
 Strength: 52318.0snT  
 Dip Angle: 65.81°  
 Date: 1/19/2011  
 Model: IGRF2010



Design: Actual (V-6-9-17/Wellbore #1)

Created By: Sarah Webb Date: 16:49, May 08 2012

THIS SURVEY IS CORRECT TO THE BEST OF  
 MY KNOWLEDGE AND IS SUPPORTED  
 BY ACTUAL FIELD DATA